





WELL "B"

RECEIVED  
SEP 27 1977

<u>MATERIAL</u>	WATER RESOURCES DEPT SALEM, OREGON	<u>FROM</u>	<u>TO</u>
SOFT BROWN CLAYEY SILT		0'	25'
BROWN SILTY SAND		25'	34'
BLACK SAND AND GRAVEL		34'	36'
BLACK SAND & GRAVEL INTERMIXED WITH BLUE SILTY CLAY		36'	39'
WELL GRADED SANDY GRAVEL		39'	51
BLUE-GREY SILTY SAND		51	54

RECEIVED

AUG 14 2002

WATER RESOURCES DEPT.  
SALEM, OREGON

WELL CASING & SCREEN

- 1 1/4" INSIDE DIAMETER PVC PIPE
- 1/4" WALL THICKNESS
- 10' LENGTH OF SLOTTED SECTION (FROM 39' TO 49' DEPTH)
- 3/16" SLOT WIDTH
- 2 1/4" SLOT LENGTH
- 34 SLOTS/ROW/LIN. FT. OF PIPE
- 8 ROWS OF SLOTS AROUND PIPE

Application No. G-8470  
Permit No.

RECEIVED  
AUG 22 1977  
WATER RESOURCES DEPT  
SALEM, OREGON

CONSTRUCTION

- WELL DRILLED WITH 30" BUCKET AUGER
- 3/8" MINUS 'GRIT' PLACED AS GRAVEL PACK AROUND LOWER PORTION OF PIPE.
- WELL SEALED WITH CEMENT FROM LAND SURFACE TO 13' DEPTH.
- WELL DRILLED 12 MARCH 1973