

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

Bent

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

(Please type or print) (Do not write above this line)

State Well No. 13/54-32M

State Permit No. G 6827 well # 2

RECEIVED
JAN 8 1968
G-4331

(1) OWNER:

Name Leighton Davis Box 127
Address Route 2 Corvallis, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
8" Diam. from 0 ft. to 114 ft. Gage STD
" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.

Type of perforator used acetylene torch
Size of perforations 1/4 in. by 6 in.
64 perforations from 39 ft. to 47 ft.
48 perforations from 71 ft. to 77 ft.
88 perforations from 101 ft. to 112 ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name _____ Model No. _____
Type _____
Diam. Slot size _____ Set from _____ ft. to _____ ft.
Diam. Slot size _____ Set from _____ ft. to _____ ft.

(8) WATER LEVEL: Completed well.

Static level 20 1/4 ft. below land surface Date 11-7-67
Artesian pressure _____ lbs. per square inch Date _____

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No. If yes, by whom?
Ball test 15 gal./min. with 3 ft. drawdown after 2 hrs.
Artesian flow _____ g.p.m. Date _____
Temperature of water 54 Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 20ft. ft.
Diameter of well bore to bottom of seal 11 in.
Were any loose strata cemented off? Yes No Depth _____
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(11) LOCATION OF WELL:

County Benton Driller's well number _____
1/4 1/4 Section 32 T. 12S R. 5W W.M.
Bearing and distance from section or subdivision corner _____

(12) WELL LOG:

Diameter of well below casing _____

Depth drilled 114 ft. Depth of completed well 114 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
topsoil	0	3	
brown clay	3	8	
yellow clay	8	24	
cemented gravel & coarse sand 4"	24	35	
sand and gravel medium	35	46	
light grey clay tough	46	60	
grey clay sandy	60	71	
sand and gravel	71	76	
grey clay	76	95	
sand and gravel & wood	95	112	
grey tough clay	112	114	

Work started 10-30-67 19 Completed 11-7-67 19

Date well drilling machine moved off of well 11-7-67 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Raymond C. Gellatly Date 1-4-68 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 76

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Raymond C. Gellatly (Type or print)
(Person, firm or corporation)

Address Box 1 Philomath, Oregon

[Signed] Raymond C. Gellatly (Water Well Contractor)

Contractor's License No. 77 Date 1-4-68 19