NOTICE TO WATER WELL CONTINCIOR  The original and first copy of this report  are to be filed with the	LL REPORT	3
water resources department A/2 9 1980 (Please tyles) of well completion.	OREGON BEAT State Well No. 12/60	W-11d
within 30 days from the date RESOUR	pe or print)	
within 30 days from the date MESOURCES (Do not write a property of well completion.  SALEM, OREGON  (1) OWNER:	above this line) State Permit No.	
(1) OWNER.		
( )	(10) LOCATION OF WELL:	
Name City of Philomath	County Bentoh Driller's well number	· · · · · · · · · · · · · · · · · · ·
Philometh Orogon 97370	SE 14 SE14 Section 11 T. 125R. 6W W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
Rotary D Oriven D	Depth at which water was first found 10 ft.	
Cable	Static level 3 ft. below land surface. Date	1-17-80
Total Test Well   Other	Artesian pressure lbs. per square inch. Date	. –
CASING INSTALLED: Threaded Welded W. Welded D. Threaded D. Welded D. Threaded D. Welded D. Threaded D. Threaded D. Welded D. Threaded D. Welded D. Threaded D. Threaded D. Welded D. Threaded D. Welded D. Threaded D. Threaded D. Welded D. Threaded D. Threaded D. Welded D. Threaded D. Threaded D. Threaded D. Welded D. Threaded D.	(12) WELL LOG: Diameter of well below casing	10 in
" Diam. fromft. toft. Gage	Depth drilled 170 ft. Depth of completed well	170 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure	of materials:
DEDECRATIONS	with at least one entry for each change of formation Report as	r penetrated,
(6) PERFORATIONS: Perforated? Yes   No.	position of Static Water Level and indicate principal water-be	earing strata.
Type of perforator used MI/IS Khife	MATERIAL From To	o SWL
Size of perforations 7/4 in. by 3 in.  190 perforations from 50 ft. to 138 ft.	5011 0 2	
	Clax Brown Sandy 2 10	5
perforations from ft. to ft	Clax 31-0144 4/9126 210 2	3
	Clay yellow w grave 1 27 3	<del>7</del> ——
(7) SCREENS: Well screen installed?   Yes W No	Clay Blue Black grovel 31 33	<del>- 31</del>
Manufacturer's Name	Clay B/4 35 39	7
Type Model No Diam Slot size Set from ft. to ft.	clay Gray 39 4°	7
Diam. Slot size Set from ft. to ft.	Clay Blut 4/grove 1 47 63	7
	13 CA 5 13 AS 9 AT 67 75	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	Black Sand 124 16	-
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Clay w/grove/ SHLL 107 185	=
d: 40 gal./min. with 120 ft. drawdown after / hrs.	Basalt Broken 115 118	7
II The state of th	gravel centented 118 12	3
II	Silt clay w/ wood & grovel 123 12	8
Bailer test gal./min. with ft. drawdown after hrs.	13/ack sand 12% 12	7
Artesian flow g.p.m.	Surveilley w/grove/ 130 140	0
iperature of water Depth artesian flow encountered ft.	Work started Basatt 19-19 Completed 17 C	/3
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1980
Well seal-Material used Cement	Drilling Machine Operator's Certification:	O
Well sealed from land surface to	This well was constructed under my direct sun	ervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are tr best knowledge and belief.	cue to my
Diameter of well bore below sealin.	rg: mad 1 (0 / 1/200 // 4 m)	3, 1980
Number of sacks of cement used in well seal	(Diming Machine Operator)	1
How was cement grout placed? Pressure pumped	Drilling Machine Operator's License No	
	Water Well Contractor's Certification:	<u> </u>
	. This well was drilled under my jurisdiction and this	s report is
Was a drive shoe used? Yes   No Plugs Size: locationft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water?   Yes No	Name MAH WE Drilling T	NC s
Type of water? depth of strata	Address 7275 NW Appalopsa	Corvall
Method of sealing strata off	[Signed] Toroy W Mulos Kit	<u> </u>
Was well gravel packed? Tyes Tro Size of gravel:	(Water Well Contractor)	
Gravel placed fromft. toft.	Contractor's License No. 23/ Date 1-33	, 19 8O