NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

BOWWATER WELL REPORTE CEIVED

STATE OF OREGON JUL 131976 State Well No.

(Please type or print) ATFR RESCURCE State Permit No. 125/6W34

(Do not write above this line) SALEM. ONECON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Tom Evans	County Benton Driller's well number	
Address Rt. 3 Box 414C	1/4 1/4 Section 21 T. 128 R. 6W W.M.	
Corvallis, Ore. 97330	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	- Control Control	
New Well 🗗 Deepening 🗌 Reconditioning 🗎 Abandon 🗀	- 1.8° ±	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 23	
Rotary Driven	1 /00 /m/	
Cable 1 Setted	Static level 15 ft. below land s	surface. Date 4/29/16
Bored Irrigation West Well Other	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded B	(12) WELL LOG: Diameter of well below casing 8th	
(5) CASING INSTALLED: Threaded D Welded 5: 250		
"Diam. fromft. toft. Gage	Depth drilled 30 ft. Depth of completed well 30 ft.	
" Diam. fromft. toft. Gage	with at least one entry for each change of formation. Report each change in	
(C) DEDECD A MICANG.		
(6) PERFORATIONS: Perforated? X Yes \(\square\) No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used acetylene	MATERIAL	From To SWL
Size of perforations in. by 6 in.	topsoil	0 2
28 perforations from 22 ft. to 28 ft.	sand & gravel	2 6
perforations fromft. toft.	cemented sand & gravel	6 20
perforations from ft. to ft.	loose sand & gravel	
(7) SCREENS: Well screen installed? I Vas 17 No.	baring 100 gpm	20 28
(1) SCREENS: Well screen installed? Yes Kno Manufacturer's Name	gray clay	28 30
Type Model No.		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom?		
Table .		
The state of the s	575	
" " " " " " " " " " " " " " " " " " " "	The state of the s	
		· ·
aw and down after — His.		
tesian flow g.p.m.		
temperature of water 51 Depth artesian flow encountered ft.	Work started 1/26/ 19 76 Complete	ed 11/29/ 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4/29/19 76
Well seal—Material usedcoment	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belder.	
Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks	[Signed] July S Walter Date 5/28/, 1976.	
Number of sacks of cement used in well seal sacks	l	
	Drilling Machine Operator's License No503	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is	
of water lbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	NameRaymond C. Gellatly & Ronald S. Witham (Person, firm or corporation) (Type or print)	
Type of water?depth of strata	Address P.O. Box 1, Philomath, Ore. 97370	
Method of sealing strata off	aumu 10	Holland.
Was well gravel packed? ☐ Yes 🗵 No Size of gravel:	[Signed] (Water Well Control	ictor)
Gravel placed from ft. to ft.	Contractor's License No77 Date	5/28/ ,19.76