

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

RECEIVED

WATER WELL REPORT

*Bent
6034*

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

DEC 1 1977

STATE OF OREGON
(Please type or print)

State Well No. 12S/6W-28

State Permit No. _____

DR: S (Do not write above this line)

EM. OREGON

(1) OWNER: Lot 36
Name Double D. Contractors
Address 999 N.W. Circle Blvd.
Corvallis, Oregon 97330

(10) LOCATION OF WELL:
County Benton Driller's well number S/112/K
¼ ¼ Section 28 T. 12S R. 6W W.M.
Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(11) WATER LEVEL: Completed well.
Depth at which water was first found 68 ft.
Static level 57 ft. below land surface. Date 10/21/77
Artesian pressure lbs. per square inch. Date

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 425 ft. Depth of completed well 425 ft.

CASING INSTALLED:
6" Diam. from 0 ft. to 35 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

MATERIAL	From	To	SWL
Brown sticky clay	0	3	
Brown sandy clay	3	8	
Brown sandstone (soft)	8	13	
Light grey sandstone (hard)	13	126	
Dark grey sandstone	126	165	
Dark grey sandstone (broken)	165	170	
Light grey sandstone W/quartz	170	228	
Brown sandstone (cong)	228	255	
Light grey sandstone W/cuartz	255	287	
Brown sandstone (cong)	287	301	
Light grey sandstone W/quartz	301	425	

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

Work started 10/21/77 Completed 10/27/77
Date well drilling machine moved off of well 10/27/77

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" Tested with air: could fluctuate "
Ballix test 50 gal./min. with 27 ft. drawdown after 4 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.
[Signed] *Gay Thomas* Date 10/31/77
(Drilling Machine Operator) 689
Drilling Machine Operator's License No. _____

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 34 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed?

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.
Name Corvallis Drilling Co. Inc.
(Person, firm or corporation) (Type or print)
Address 3440 SW 3rd St. Corvallis, Oregon 97330
[Signed] *Blair A. Kinsky*
(Water Well Contractor)
Contractor's License No. 560 Date 10/31/77, 19____

Mixed and poured from top
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from ft. to ft.