NOTICE TO WATER WELL CONTRACTOR
The original and first copy of his report are to be filed with the first CP FIRST WELL REPORT

STATE OF OREGON

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
Within 30 days from the date

JUL 1 4 1977

STATE OF OREGON

(Please type or print)

of well completion TER RESOURCES DEBTot write above this line)

Bent	State Well No. 135/5w-1 &)C
6193	State Permit No.	••

WATER RESOURCES DEPT.			_
(1) OWNER:	(10) LOCATION OF WELL: Benton	. 8377	
Name Bobb F. Brown	County Driller's well nu	ımber	
Address 3211 N.W. McKinley	SW 1/4 NW 1/4 Section 1 T. 13S	R. <u>5W</u>	W.M.
Corvallis, Oregon 97330	Bearing and distance from section or subdivision	on corner	
TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon Reconditioning Abandon If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	24	77/77
Rotary Driven Domestic Industrial Municipal	Static level 16 ft. below land s	urface. Date	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well b	alow assing	12
" Diam. from0	Depth drilled 40 ft. Depth of complete	4.0	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
" Diam. from ft, Gage ft, Gage	and show thickness and nature of each stratus	m and aquifer p	enetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prin		
of perforator used Torch Cut	MATERIAL	From To	SWL
Size of perforations 1/4 in. by 6 in.	Top Soil	0 3	
140 perforations from 20 ft. to 40 ft.	Sandy Clay	3 16	1
perforations fromft. toft.	Brown Clay & Gravel	16 24	16
perforations from	Med. Sand & Gravel	24 38	
(7) SCREENS: Well screen installed? Yes Yes	Blue Clay	38 40	
			
Manufacturer's Name Model No			 -
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			1
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			-
Was a pump test made? ☐ Yes 汉 No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
и и и			
Bailer test 90 gal./min. with X3 ft. drawdown after 4 hrs.		 	
Artesian flow g.p.m.			
perature of water 52 Depth artesian flow encountered ft.	Work started 7/6 19 77 Complete	7/7	19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/7	19 77
Coment	Drilling Machine Operator's Certification:		
Well seal—Material used Comolie Well sealed from land surface to 18 ft.	This well was constructed under my	direct supe	rvision.
Diameter of well bore to bottom of seal 16 in.	Materials used and information reported best knowledge and belief.	above are tru	e to my
Diameter of well bore below seal12 in.	[Signed] (Unual Com	Date	2, 19,22
Number of sacks of cement used in well seal	(Drilling Machine Operator)	606	,,
was cement grout placed?	Drilling Machine Operator's License No.		
hand mixed and hand placed	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi true to the best of my knowledge and bel		report is
Was a drive shoe used? 🙀 Yes 🗋 No Plugs Size: location ft.	Name Schoen Electric Inc		
Did any strata contain unusable water? Yes XX No	(Person, firm or corporation)	(Type or pr	
Type of water? depth of strata	Address 626 Wo Queen Albany	y, Oregon	97321
Method of sealing strata off	[Signed] Amy Elle	~	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	actor)	7-
Gravel placed from ft. to ft.	Contractor's License No	1116	, 19 / _