NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT STATE OF OREGON (Please type or print) STATE FINGINEER PORT IN TO STATE OF OREGON (Please type or print) STATE FINGINEER PORT IN TO S

(Please type or print)

(Do not write above this line)

SALEM. OREGON

gat.	DALEM, DIREGUL	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Corvallis School District 509J (Invale)	County Benton Driller's well no	umber F/54/A
Address 1555SW 35th St	14 14 Section 7 T. 139	3 R. 5W W.M.
Corvallis, Oregon 97330	Bearing and distance from section or subdivisi	_
(2) TYPE OF WORK (check):		
New Well  ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 33 ft.	
Rotary Driven Domestic M Industrial Municipal		surface. Date 9/5/74
Cable		re inch. Date
CASING INSTALLED: Threaded   Welded   Welded   Welded   Welded   Welded   Welded   Welded   Case   C	(12) WELL LOG: Diameter of well below casing6.	
-	Depth drilled 39 ft. Depth of completed well 39 ft.	
	Formation: Describe color, texture, grain size	
DEDEOD AUTONS.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
PERFORATIONS: Perforated? Yes No.		<del>, , , , , , , , , , , , , , , , , , , </del>
Type of perforator used torch	MATERIAL	From To SWL
Size of perforations 4 in. by 4 in.	brown clay soil	0 3
# 24 perforations from	yellow sticky clay	<del>                                     </del>
perforations fromft. toft.	brown clay soil yellow sand & gravel	<del>                                     </del>
perforations from ft. to ft.	gray claystone	15 15½ 15½ 15½ 15½ 15½ 15½ 15½ 15½ 15½ 1
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	gray sand	20 25
Manufacturer's Name	gray sandy clay	25 30
Type Model No	sand & gravel	30 39
Diam Slot size Set from ft. to ft.	50110 00 820 02	)0 ))
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
	7	
Was a pump test made?   Yield:   Yield		
Yield: 30 gal./min. with 14 ft. drawdown after 24 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.	-	
Artesian flow g.p.m.		<u>L </u>
nperature of water Depth artesian flow encountered ft.	Work started 9/5/74 19 Complet	ed 9/6/74 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/6/74 19
Well seal—Material usedcement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of seal10	best knowledge and belief.	<b>Y</b> - 1 - 1 - 1
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date9/10/7419
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	Name Corvallis Drilling Co. Inc.	
Did any strata contain unusable water?   Yes   No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 3440 SW 3rd St. Corvallis, Ore. 97330	
Method of sealing strata off	[Signed] Selazione A K	19
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed]	ractor)
Gravel placed from ft. to ft.	Contractor's License No560 Date	9/10/74, 19