

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
MAY 20 1970

STATE ENGINEER WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON
within 30 days from the date
of well completion.

STATE ENGINEER OF OREGON
(Please type or print)
SALEM, OREGON

State Well No. 13/5W-35 ac

State Permit No. G5244

(1) OWNER:

Name Mr. Dan Tracer #1
Address Route 3, Junction City, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
10" Diam. from +6" ft. to 29 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Torch
Size of perforations 3/8 in. by 6 in.
160 perforations from 18 ft. to 28 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 5'6" ft. below land surface Date 5/5/70
Pneumatic pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom Driller
Yield: 500 gal./min. with 6'6" ft. drawdown after 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 18 ft.
Diameter of well bore to bottom of seal 14 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Benton Driller's well number
1/4 1/4 Section 35 T. 13S R. 5W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 29 ft. Depth of completed well 29 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL.
Soil	0	5	
Sand & Gravel, tight	5	14	
Sand & Gravel, loose	14	20	5'6"
Sand & Gravel with clay	20	22	
Sand & Gravel, loose	22	24	
Sand & Gravel w/clay	24	25	
Sand & Gravel, loose	25	27	
Sand & Gravel, w/clay	27	27.6"	
Sand & Gravel, loose	27.6	29	5'6"
Cemented gravel	29		

Work started 5/4 19 70 Completed 5/5 1970
Date well drilling machine moved off of well 5/6 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Carl Gitcher Date 5/18, 1970.
(Drilling Machine Operator)

Drilling Machine Operator's License No. 386

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Fitcher Pump & Drilling Company
(Person, firm or corporation) (Type or print)
Address 255 W. 5th St, Junction City, Oregon
[Signed] Carl Gitcher
(Water Well Contractor)
Contractor's License No. 494 Date May 18, 1970