۲	13cm + 6343	
NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be SEP 9 1965 WATER WE		-36.
The original and first copy SIP 9 1965 WATER WE of this report are to be filed with the SIP 1965 WATER WE STATE ENGINEER, SALEM, OREGON 97310 SNGINEER TATE OF within 30 days from the date 15 M CRUBON (Please ty of well completion.	FOREGON FEB 11 1966 State Well No.	
(1) OWNER: ocker Bros., or	(11) WELL TESTS: EG Blawdown is amount water level is lowered below static level	
Name C. C. Lindseth / Address Rt. 3 Junction City, Ore.	Was a pump test made?Yes XNoIf yes, by whom?Yield:gal./min. withft. drawdown after	hrs.
(2) LOCATION OF WELL:	" " " " " "	"
County Benton Driller's well number	Bailer test 9000 gal./min. with () ft. drawdown after]	hrs.
¼ ¼ Section 35 T. /3.5 R. 5W W.M. Bearing and distance from section or subdivision corner	Artesian flowg.p.m. DateTemperature of waterWas a chemical analysis made? [] Yes	No No
	(12) WELL LOG: Diameter of well below casing <u>12</u>	58
	Depth drilled 35 ft. Depth of completed well 35	ft.
	Formation: Describe by color, character, size of material and structur show thickness of aquifers and the kind and nature of the material i stratum penetrated, with at least one entry for each change of form	re, and in each mation.
(3) TYPE OF WORK (check):		то
New Well 🛛 Deepening 🗆 Reconditioning 🗆 Abandon 🗋 I donment, describe material and procedure in Item 12.	Top soilbrown clay0Sandy clay3Sand & gravel8	<u>3</u>
(4) PROPOSED USE (check): (5) TYPE OF WELL:		35
Domestic Industrial Municipal Rotary Driven Irrigation Test Well Other Dug Jetted		
(6) CASING INSTALLED: Threaded Welded		
<u>1.2.</u> " Diam. from		
(7) PERFORATIONS: Perforated? 🛆 Yes 🗆 No		
Type of perforator used torch		
<u>Size of perforations</u> <u>in. by 12</u> in. 		
ft. to ft. to ft.		
perforations from ft. to ft.		·
perforations from ft. to ft.		· · ·
(8) SCREENS: Well screen installed? Ver C No		·
(6) SCREENS: Well screen installed? Yes No Manufacturer's Name		
Model No		
Slot size ft. to ft. to ft.	Work started 7/26/65 19 Completed 7/29/65	19
Diam Slot size Set from ft. to ft.		19
(9) CONSTRUCTION:	(13) PUMP:	
Well seal-Material used in seal Puddled clay&	Manufacturer's Name	
Depth of seal	Туре:	
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:	
Were any loose strata cemented off? □ Yes ⊠ No Depth Was a drive shoe used? ∑ Yes □ No		
Was well gravel packed? Vas No Size of gravel:	This well was drilled under my jurisdiction and this reputrue to the best of my knowledge and belief.	ort is
Gravel placed from ft. to ft.	NAME "Casey Jones Well Drilling Co.	÷.,
Did any strata contain unusable water? □ Yes 沾 No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address Rt, 2 Box KYXX 695, Creswell, Oreg	jon
Method of sealing strata off (10) WATER LEVELS.	Drilling Machine Operator's Liconse No.	
(10) WATER LEVELS: Static level 12 ft. below land surface Date 7/00/45	[Signed]	
Static level 12 ft. below land surface Date 7/29/65 Artesian pressure Ibs. per square inch Date		· · · · · ·
Artesian pressure lbs. per square inch Date Contractor's License No. 103 Date 2/6/65 (USE ADDITIONAL SHEETS IF NECESSARY)		