

The original and final copies of this report are to be filed with the

RECEIVED APR 15 1971

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

Bent 6885

State Well No. 14/5W-26da

State Permit No. G 5495

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:

Name Mr. A. A. Wheeler Address Route 3, Box 681, Junction City, Oregon 97448

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [] Dug [] Driven [x] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x] 6" Diam. from 0 ft. to 27 ft. Gage 250

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Size of perforator used Torch Size of perforations 3/8 in. by 6 in. 54 perforations from 27 ft. to 23 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Driller Yield: 400 gal./min. with 8 ft. drawdown after 1 hrs.

CONSTRUCTION:

Well seal—Material used Bentonite Well sealed from land surface to 6 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal 10 lbs. sacks Brand name of bentonite Yellowstone Number of pounds of bentonite per 100 gallons of water 60 lbs./100 gals. Was a drive shoe used? [] Yes [x] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Benton Driller's well number 1/4 1/4 Section 26 T. 14S R. 5W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 10 ft. Static level 10 ft. below land surface. Date 4/3/71 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0 Depth drilled 27 ft. Depth of completed well 27 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil & sand, Sand & gravels, loose, Sand & gravels w/clay, Sand & gravels, loose, Sand & gravels w/clay.

Work started 4/2/ 1971 Completed 4/3 1971 Date well drilling machine moved off of well 4/3 1971

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Carl Gately (Drilling Machine Operator) Date 4/13, 1971

Drilling Machine Operator's License No. 386

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Pitcher Pump & Drilling Company (Person, firm or corporation) (Type or print)

Address 800 Prairie Road, Junction City, Oregon

[Signed] Carl Gately (Water Well Contractor)

Contractor's License No. 494 Date 4/13, 1971