NOTICE TO WATER WELL CONTRACTOR The original and first copy	STACE STACE		
of this report are to be	LL REPORT	7/2 70	
state engineer, salem, oregon 97316, PR 8 1968 Flease ty	F OREGON 010030 State Well No.	5/2-/N	
within 30 days from the date of well completion. TE ENGINEER	above this line) State Permit N	o	
or well completion. OF THE ENGINEER			
(1) OWNER:	(11) LOCATION OF THE L.		
A 7 7	(11) LOCATION OF WELL:		
R+ 2 Bo+ 120	County Clacksman Driller's well no	, OF	
Molalla, Oregon 97038	SE ¼ SE ¼ Section 7 T. 58	$S_{R.}$ $2E_{W.M.}$	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.		· · · · · · · · · · · · · · · · · · ·	
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Rotary Driven Demostic X	(12) WELL LOG: Diameter of well below casing		
Cable Discrete Domestic Discrete Municipal Discrete Dug Bored Discrete Disc	Depth drilled 138 ft. Depth of compl	eted well 138 ft.	
	Formation: Describe color, texture, grain size		
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change		
6	in position of Static Water Level as drilling pro		
59/16 Diam. from 51 ft. to 138 ft. Gage 10 Gg	MATERIAL	From To SWL	
" Diam. from ft. to ft. Gage	Top soil, brown	0 2	
PERFORATIONS: Perforated? Types No.	Clay, brown	2 4	
Type of perforator used Cut by torch	Coa rse gravel to small	4 12	
Size of perforations 1/8 in. by 5 in.	boulder size		
. 66 perforations from 55 ft. to 90 ft.	Clay, tan	12 26	
16 perforations from 114 ft. to 120 ft.	Clay, brown, Clay, brown sandy	26 35 35 46	
perforations from ft. to ft.	Clay, brown sandy Clay, brown	35 46 46 51	
perforations from	Clay, brown sandy	51 56	
perforations from ft. to ft.	Sand, med., brown	56 63 32	
(7) SCREENS: Well screen installed? Ves W No	Clay, blue	63 70	
(7) SUREENS: Well screen installed? ☐ Yes ☑ No Manufacturer's Name	Sandy, formation, black	70 73 32	
Type Model No	Clay, blue	73 84	
Diam. Slot size Set from ft. to ft.	Clay, blue, sandy	84 86	
Diam. Slot size Set from ft. to ft.	Clay, blue	86 112	
	Clay, blue, sandy	112 116	
(8) WATER LEVEL: Completed well.	Sand, fine, black Clay, grey	116 118	
Steffic level 32 ft. below land surface Date 3/13/6	Clay, grey	118 138	
A Sian pressure lbs. per square inch Date	*		
(9) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
Yiald: gal./min. with ft. drawdown after hrs.	Work started 3/8 1968 Complete	ed 3/13 19 68	
" " "	Date well drilling machine moved off of well	3/13 ₁₉ 68	
" " " " " "			
28	Drilling Machine Operator's Certification: This well was constructed under my di	rect supervision Mate-	
Danier test gal./min. with it. drawdown after hrs.	rials used and information reported above	e are true to my best	
Artesian flow g.p.m. Date	knowledge and belief.	0/20 (0	
Temperature of water 54 Was a chemical analysis made? Vesx No	[Signed] (Drilling Machine Operator)	Date 3/19 , ₁₉ 68	
(10) CONSTRUCTION:		86	
Well seal Material used Bentonite	Drilling Machine Operator's License No	00	
Depth of sealft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdiction and this report is		
Were any loose strata cemented off? Train No Depth	True to the best of my knowledge and helief		
Was a drive shoe used? Yes 🗆 No	NAME C. G. Westerberg (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes No		- ·	
Type of water? depth of strata	Address Rt. 1, Box 151, Mul	ino, Oregon	
Method of sealing strata off	[Signed] Statester		
Was well gravel packed? ☐ Yes X☐ No Size of gravel:	(Water Well Contract	or)	
Gravel placed fromft,	Contractor's License No. 86 Date	3/19 19 68	

A