

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

CLAC 10090 RECEIVED
WATER WELL REPORT

CLAC

STATE OF OREGON JUL 8 1975 State Well No. 55/2E-10³
(Please type or print)
WATER RESOURCES DEPT.
SALEM, OREGON
(Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

010090

(1) OWNER: CAMP ONAHLEE,
Name MT. HOOD COUNCIL CAMP FIRE GIRLS
Address RT. 4, BOX 566, MOLALLA, OREGON
97038

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

CASING INSTALLED: Threaded Welded
6" Diam. from +1 ft. to 109 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 50 gal./min. with 10 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 100 ft.
Diameter of well bore to bottom of seal 6 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite BAROID
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County CLACKAMAS Driller's well number 75-28
¼ Section 10 T. 5S R. 2 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 66 ft.
Static level 45 ft. below land surface. Date 7-4-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 103 ft. Depth of completed well 103 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BOULDERS & SAND	0	20	
CEMENTED SAND & GRAVEL	20	22	
BROWN CLAY & SAND	22	26	
BLUE CLAY AND SAND	26	38	
BLACK CLAY, HARD	38	41	
BLUE CLAY & SMALL GRAVEL	41	58	
BLUE CLAY	58	66	
BLUE CLAY & SAND	66	78	45
BLUE CLAY	78	85	
BLUE CLAY & SAND	85	94	
BLUE CLAY SAND & GRAVEL	94	103	21

Work started 7-2 19 75 Completed 7-5 1975
Date well drilling machine moved off of well 7-5 1975

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Thomas Flores Date 7-6, 1975
(Drilling Machine Operator)
Drilling Machine Operator's License No. 978

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name FLORES WELL DRILLING
(Person, firm or corporation) (Type or print)
Address RT. 1, BOX 56, GERVAIS, ORE
[Signed] Thomas Flores
(Water Well Contractor)
Contractor's License No. 590 Date 7-6, 1975