

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
MAR 29 1972

WATER WELL REPORT

CLAC

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97301
within 30 days from the date
of well completion.

(Please type or print)

STATE ENGINEER
SALEM, OREGON

(Do not write above this line)

State Well No.

5/2-19db

State Permit No.

G-5675

(1) OWNER:

Name Larry Wrolstad
Address Malilla, Oreg

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
" Diam. from " ft. to " ft. Gage "250

" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with " ft. drawdown after " hrs.

" " " " " "

"Air 45 " " " " " "

Ball test gal./min. with 78 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 36 " ft.

Diameter of well bore to bottom of seal 10" to 20 ft. 9" to 36

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal 4 sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No plugs Size: location " ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: " ft.

Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County Clackamas

Driller's well number

N.W. 1/4 S.E. 1/4 Section 19 T. 5.S. R. 2.E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 180 ft.

Static level 122 ft. below land surface. Date 2/24/72

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 221 ft. Depth of completed well 221 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil red	0	1	
Clay brn.	1	2 6	
H. sandstone brn.	6 9x	10	
H. basalt grey	10	19	
M. basalt blk.	19	31	
H. basalt grey	31	82	
H. sandstone grey	82	91	
H. basalt grey	91	179	
H. basalt & green seams W.B.	179	190	
H. basalt grey W.B.	190	221	

Work started 2.23/72 19 Completed 2/24/72 19

Date well drilling machine moved off of well 2/24/72 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] C. F. Stadeli Date 2/29/72, 19...
(Drilling Machine Operator) 84

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name R. Stadeli & Sons Inc
(Person, firm or corporation) (Type or print)

Address Silverton, Oreg

[Signed] Paul R. Stadeli
(Water Well Contractor)

Contractor's License No. 296 Date 2/29/72, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP-45050-119