NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
OCT 19 1966
STATE ENGINEER
SALEM, OREGON

CLAC

WATER WELL REPORT 010331

STATE OF OREGON
(Please type or print)

State Well No. 5/2-19 R

G-3920 State Permit No.

(1) OWNER:

Name Delmar Pease

Address Rt3 Box345, Molalla, Oreg

(2) LOCATION OF WELL:

County Clackamas Driller's well number

¼ ¼ Section T. R. W.M.

Bearing and distance from section or subdivision corner

1150 ft. N. & 150 ft W. of S.E. cor sec 19 T5s R2E

(3) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

(5) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(6) CASING INSTALLED:

Threaded [] Welded [X]

6 " Diam. from 0 ft. to 20 ft. Gage .250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(7) PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(8) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Bentonite & cuttings

Depth of seal 18 ft. Was a packer used? no

Diameter of well bore to bottom of seal 9 7/8 in.

Were any loose strata cemented off? [] Yes [X] No Depth

Was a drive shoe used? [] Yes [X] No

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

(10) WATER LEVELS:

Static level 172 ft. below land surface Date 9/23

Artesian pressure lbs. per square inch Date

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " " "

" air " " "

Bailer test 50 gal./min. with 103 ft. drawdown after 1 hr.

Artesian flow g.p.m. Date

Temperature of water XX Was a chemical analysis made? [] Yes [X] No

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 275 ft. Depth of completed well 275 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Top soil brn.	0	1
Clay brn.	1	3
Med basalt grey	3	12
Hard basalt grey	12	200
Med basalt grey W.B.	200	275

Work started 9/22 1966 Completed 9/23 1966

Date well drilling machine moved off of well 9/24 66

(13) PUMP:

Manufacturer's Name ?

Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME R. Stadeli & Sons
(Person, firm or corporation) (Type or print)

Address Rt 3 Box 169, Silverton, Oreg.

Drilling Machine Operator's License No. 84

[Signed] Paul R. Stadeli
(Water Well Contractor)

Contractor's License No. 296 Date 10/18, 1966

(USE ADDITIONAL SHEETS IF NECESSARY)