NOTICE TO WATER WELL CONTRACTOR The original and first cay JUL 7 1969 WATER WELL REPORT

state engineer, salem, oregon 97310 (Please type or print) within 30 days from the date of well completion.



(1) OWNER:	(11) LOCATION OF WELL:			
Name GLAD CONST. CO.	County CLACKAMAS Driller's well number 87			
Address RT 1 Box 678	NE 1/2 NE 1/2 Section 32 T. IS R. 4E W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well				
If abandonment, describe material and procedure in Item 12.				
Rotary Driven	(12) WELL LOG: Diameter of well below casing			
Cable Domestic Lindustrial Municipal	Depth drilled 200 ft. Depth of completed well 200 ft.			
Dug Bored I Irrigation Test Well Other	Formation: Describe color, texture, grain size and structure of materials;			
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change			
6 " Diam. from 0 ft. to 200 ft. Gage 1250	in position of Static Water Level as drilling pr	oceeds. N	eport each Iote drillir	cnange
" Diam. fromft. toft. Gage	MATERIAL	From	Tó	SWL
ft. to	TOP SOIL	0	1	
PERFORATIONS: Perforated? 2 Yes [] No	BROWN CLAY	1	14	
- Salara Bara	GRAVEL AND CLAY	Li	20	
Type of perforator used MILLS KNIFF	- BOULDER	125	27	• .
Size of perforations in. by in.	CEMENTED GRAVEL	27	29	
300 perforations from 80 ft. to 190 ft.	BOULDERS	29	43	
perforations from ft. to ft.	COMENTED GRAVEL	43	52	
perforations from ft. to ft.	CEMENTED GRAVEL			
perforations fromft. toft.	AND BOULDERS	52	80	
perforations from	CEMENTED GRAVEL	80	97	53
(7) SCREENS: Well screen installed? Yes S. No	BOULDERS	97	99	53
Manufacturer's Name	CEMENTED GRAVEL	99	103	53
Type Model No.	CLAY	103	106	53
Diam. Slot size Set from ft. to ft.	COMENTED GRAVEL	106	1162	25
Diam Slot size	BOULDIES	116	120	<u> 53</u>
(2) WATER I EVEL. Completed well	COMENTED CARNEL	120	13/	53
(8) WATER LEVEL: Completed well. Static level 53 ft below land surface Date 6/12/14	AND BOULDERS	120	1000	- Com
At below and surface Date 118/01	Consession of Oh	156	740	22
sian pressure lbs, per square inch Date	CEMENTED GRAVEL	130	100	<u>D</u> >
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? [] Yes 'E. No If yes, by whom?		ار		
Yield: gal./min. with ft. drawdown after hrs.	Work started 5/21 1969 Complet	ed 6/1	3	1969
" " "	Date well drilling machine moved off of well	6/13		1960
" " " " "	Drilling Machine Operator's Certification:	7		
Bailer test 40 gal./min. with 40 ft. drawdown after hrs.	This well was constructed under my dirials used and information reported above	irect sup	ervision.	Mate-
Artesian flow g.p.m. Date	knowledge and belief.	/e are u	lue to m	y best
Temperature of water 56° Was a chemical analysis made? Yes No	[Signed] Corilling Madnine Operator)	Date	/2	19.69
(10) CONSTRUCTION:		/	329	
Well seal—Material used CEMENT	Drilling Machine Operator's License No.		<i></i>	
Depth of sealft	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off? No Depth Depth	true to the best of my knowledge and belief.			
Was a drive shoe used? AYes No	NAME (Person, firm or corporation)	Type (Type	or print)	.
Did any strata contain unusable water? Yes No	Address 5365 SE HILLWO	1 00	N	کا ہسلان ۵
Type of water? depth of strata	The state of the s	K.i.K	tirmi	TINI
Method of sealing strata off	[Signed]	Qe		
Was well gravel packed? Wes No Size of gravel:	(Water Well Contrac	tor)		10
Gravel placed from 5/ ft.	Contractor's License No. 462 Date	1/2		19 64
(IICE A DEPUTEDA A COL				