

NOTICE TO WATER WELL CONTRACTOR:
The original and first copy
of this report are to be
filed with the

RECEIVED
OCT 21 1971

WATER WELL REPORT

CLAC

4/3-27

STATE OF OREGON
STATE ENGINEER, SALEM
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

(Do not write above this line)

State Well No. 011419

State Permit No.

(1) OWNER:

Name Merlin Mc Gladney
Address Box 280 Rt #1
Clatsop, Ore.

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 313 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

Bailer test 12 gal./min. with 10 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water 54° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used 3F Sucker Clay

Well sealed from land surface to 40 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clatsop Driller's well number
1/4 1/4 Section 27 T. 44 R. 36 W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft.

Static level 295 ft. below land surface. Date 10/18/71

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 320 ft. Depth of completed well 320 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay	3	18	
Rock	18	35	
Brown Clay & Gravel	35	60	
Brown Clay	60	90	
Light Gray Clay	90	100	
Brown Clay & Gravel	100	145	
Blue Clay	145	225	
Drainage Brown Clay	225	275	
Blue Clay & Gravel	275	300	
Drainage Brown Clay & Gravel	300	319	
Gravel	319	320	

Work started Oct. 7 19 71 Completed 10/18 19 71

Date well drilling machine moved off of well 10/18 19 71

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] J.F. Terrell Date 10/19, 19 71
(Drilling Machine Operator)

Drilling Machine Operator's License No. 179

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name J.F. Terrell Well Drilling (Type or print)
(Person, firm or corporation)

Address 8425 Wheatland Rd N. Salem, Ore. 97303

[Signed] Mrs. Zona D. Terrell
(Water Well Contractor)

Contractor's License No. 460 Date 10/18, 19 71