WATER WELL REPORT STATE OF OREGON

CLAC RECEIVED
DEG 2.9 1981
WATER RESOURCES DE

State Permit No.

WATER RESOURCES DEPT

TAL.	Will Overand		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Canby Grove Conference Center	County Clackamas Driller's well number 35	81	
Address 7501 Knights Bridge Rd.	4 4 Section 3.2 T. 3 S. R. 1 E.	, W,M.	
City Canby State Oregon	Tax Lot # Lot Blk Subdivis		
(2) TYPE OF WORK (check):	Address at well location: 7501 Knights Bridge Rd.,		
	Canby, Oregon		
New Well Deepening □ Reconditioning □ Abandon □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.		
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found	. 20 ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 16 ft. below land surface. Dat		
Rotary Air 🗗 Driven 🗆 Domestic 🗆 Industrial 🗆 Municipal 🗆	Artesian pressure lbs. per square inch. I		
Rotary Mud	(40) 1177777700	0	
		75 ft.	
(5) CASING INSTALLED: Steel X Plastic Threaded Welded X	Depth drilled 75 ft. Depth of completed well Formation: Describe color, texture, grain size and structure of mater		
Threaded \square Welded \square . Welded \square . Suppose \square . Welded \square . Suppose \square . Suppo	thickness and nature of each stratum and aquifer penetrated, with at 1	east one entry	
"Diam fromft. toft. Gauge	for each change of formation. Report each change in position of Stati and indicate principal water-bearing strata.	c Water Level	
LINER INSTALLED:		•	
	MATERIAL From To	SWL	
ft. Cauge	Sand, Soil 0 4		
(6) PERFORATIONS: Perforated? □ Yes 🛚 No	Clay Brown & Gravel Large 4 20		
Type of perforator used	Sand Grey Coarse 20 28 Clay Grey 28 37		
Size of perforations in. by in.	Sand Grey Fine 37 53		
ft. to ft.	Sand Grey Med. 53 63		
perforations fromft. toft.	Sand Brown Med. 63 65		
perforations from ft. to ft.	Sand Grey Med. to Coarse 65 67		
(7) SCREENS: Well screen installed?	Sand Brown Med. 67 69		
Manufacturer's Name Johnson	Sand Grey Med. 69 72		
Type Stainless Model No.	Sand Grey Med., some Gravel	16'	
Diam. Slot Size 25. Set from 65. ft. to 75. ft.	72 75	16'	
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	, 444		
a pump test made? XYes \(\subseteq \) No If yes, by whom? \(D \) & A Pump			
125 gal/min with 49 ft. drawdown after 1 hrs.			
Air test gal./min. with drill stem at ft. hrs.	and the second of the second o		
Bailer test gal/min. with ft. drawdown after hrs.			
Artesian flow g.p.m.	22' 1		
erature of water Depth artesian flow encountered ft.	10 10 01		
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \)	Work started 10-19 19 81 Completed 10-22 1981 Date well drilling machine moved off of well 10-23 1981		
Well seal—Material used Cement w/5% Bentonite			
Well sealed from land surface to	Drilling Machine Operator's Certification:		
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal8 in.	[Signed] 12-2810 8/		
Number of sacks of cement used in well seal 20 sacks	(Drilling Machine Operator)	19.7.	
How was cement grout placed? Pumped	Drilling Machine Operator's License No. 2224		
and the state of t	Water Well Contractor's Certification:		
The second secon	This well was drilled under my jurisdiction and this report is true to		
Was pump installed YesType Sub HP 15 Depth 68 ft.	the best of my knowledge and belief.		
Was a drive shoe used? ✓ Yes □ No Plugs Size: location ft.	Name Skyles Drilling, Inc. (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? ☐ Yes ☐XNo	Address 1169 Molalla Ave Oregon City OR		
Type of Water? depth of strata			
Method of sealing strata off	[Signed] (Water Well Contractor)	*************	
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	Contractor's License No 553 Date 12 - 2	19.8-1	