CLAC DBSERVATION WELL

STATE ENGINEER WATER WELL REPORT File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE OF OREGON State Permit No. G-1246

(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static l	water level is
Name V.A.Ditomaso Christ T. Schlung	A A No. If yes, by who	m? Driller
Address P.O.Box 912	Yield: 225 gal./min. with 59 ft. drawdo	
Canby, Oregon	39 99	
(2) LOCATION OF WELL:	n n	
County Clackamas Owner's number, if any—	Bailer test gal./min. with ft. drawdown after hr	
1/4 1/4 Section T. R. W.M	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water 56 Was a chemical analysis n	nade? 🗌 Yes 🖳 Ne
	(12) WELL LOG: Diameter of well	10 inches
Permit # G=1246	Depth drilled 190 ft. Depth of completed v	_
Termit # W=1240	Formation: Describe by color, character, size of materishow thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	ial and structure, and the material in each
	MATERIAL	
(A) MY (DY) AN AVIONAL (I I I)		FROM TO
(3) TYPE OF WORK (check):	Top Soil	0 4
New Well. Deepening Reconditioning Abandon pandonment, describe material and procedure in Item 11.		4 9
bandonment, describe material and procedure in item 11.	Dry gravel	9 25
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Dry Gravel & Clay	25 54
Domestic Industrial Municipal Rotary Driven	Brown gravel & Clay	54 66
Irrigation Test Well Other Dug Bored	Brown Sand & Gravel Sandy Clay	66 80
7	Gravel & Sand	80 87
(6) CASING INSTALLED: Threaded Welded	777 07	97 93
10 " Diam. from Top ft. to 100 ft. Gage 31.20	(CINDERS) ???	93 120
"Diam. from ft. to ft. Gage	Blue Clav	120 121
" Diam. from ft, to ft, Gage	. Take VIAV	151 190
(7) PERFORATIONS: Perforated? Yes No Type of perforator used SIZE of perforations 1/4 in. by 1½ in. perforations from ft. to ft. 300 perforations from 59 ft. to 76 ft. 200 perforations from 87 ft. to 93 ft. perforations from ft. to ft. perforations from ft. to ft.		
(8) SCREENS: Well screen installed Yes X No		
Manufacturer's Name	2 .	
The Model No.		
n		
Dram. Slot size Set from ft. to ft.	Work started April 6 19 59 Completed5-	2-59 19
(4) (4) (4)		
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? Yes Size of gravel:	Manufacturer's Name	.com/orespecial/assistations
Gravel placed fromft_ to ft.	Type:	
Was a surface seal provided? A Yes □ No To what depth?	W. II D. III . I GO .	
Material used in seal— prill autings Did any strata contain unusable water? Yes No	Well Driller's Statement:	
Type of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Method of sealing strata off		
	NAME Max Wymore (Person, firm, or corporation) (T	ype or print)
(10) WATER LEVELS:	D+ 0 Down 001 Colom	Oregon
Static level 59ft. below land surface Date May 2,5	The state of the s	7
Artesian pressure Ibs. per square inch Date	Driller's well number \\ \dagger 485	-
Tog Accorded have	922 8 hours 0	

__ Date __<u>May 2</u> , 59 19.....