NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

CLAC State Well No. _3 State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	D 255 70	
Name DAVID ADAMS		mber D-255-79	
Address 23149 S. HAINES RD.	NE 14 NE 14 Section 34 T. 3S	R. 1E W.M	
CANBY, OREGON 97013	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well 🕱 Deepening 🗌 Reconditioning 🗍 Abandon 🗎			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 80	f	
Rotary Driven Domestic X Industrial Municipal	Static level 91 ft. below land s	urface. Date 8-6-7	
Cable	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded EX 250 140 ft. Gage 188 "Diam. from 135 ft. to ft. Gage 188 "Diam. from ft. to ft. Gage PERFORATIONS: Perforated? Kes No.	(12) WELL LOG: Diameter of well below casing 6 Depth drilled 159 ft. Depth of completed well 159 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used torch	MATERIAL	From To SWL	
Type of perforations 10 torch Size of perforations 10 in. by 3/16th in. 48 perforations from 139 ft. to 159 ft.	topsoil	0 3	
48 perforations from 139 ft. to 159 ft.	clay brown	3 15	
perforations from ft. to ft.	sandy brown	15 25 25 25 105	
perforations from	gravel cemented	105 139	
(7) SCREENS: Well screen installed? Yes Who	clay blue	139 145	
Manufacturer's Name	sandstone black	145 152	
Type Model No.	clay brown sandstone black coarse	152 158	
Diam. Slot size Set from ft. to ft.	clay gray	158	
Diam ft. to ft.	CTAY GTAY		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED		
was a pump test made? Yes Who If yes, by whom?	/AUG 5 - 1979		
gai./min. with 1t. drawdown and	WATER RESOURCES DEPT		
" " "	SALFM, OREGON		
н н н			
Bailer test gal./min. with ft. drawdown after hrs.	n.e		
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 8-3 19 79 Complete	ed 8-4 179	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	86 19 7	
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Drilling Machine Operator) Drilling Machine Operator's License No. 1290		
·	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes [] No Plugs Size: location ft.	true to the best of my knowledge and belief. Name S & M DRILLING & SUPPLY, INC.		
Did any strata contain unusable water? Tyes Vo	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 399 S.E. Walnut St.	Canby, Or.	
Method of sealing strata off	Isimus (O BITTE //2-	o	
Was well gravel packed? ☐ Yes 🖔 Size of gravel:	[Signed] (Water Well Control	ractor)	
Gravel placed from ft to ft.	Contractor's License No. 497. Date	8-6 19"	
Graver practu mom	1 David of the same of t		