NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this like)

CLAC State Well No

012076 State Permit No.

1) OWNER:	(10) LOCATION OF WELL:	
Jack Parsons	County Clackamas Driller's well number 2332	
Address 25460 S.W. Baker Rd.	14 14 Section 34 T.3S R. 1E W.M.  Rearing and distance from section or subdivision corner	
Sherwood, Oregon 97140		
2) TYPE OF WORK (check):		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 119 ft.	
tary ☐ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐	Static level 80 ft. below land surface. Date 10/8/80	
	Artesian pressure lbs. per square inch. Date	
5) CASING INSTALLED: Threaded \( \bar{\mathbb{D}} \) Welded \( \bar{\mathbb{D}} \) \( \bar{\mathbb{D}} \) Threaded \( \bar{\mathbb{D}} \) Welded \( \bar{\mathbb{D}} \) \( \bar{\mathbb{D}} \) Diam. from \( \bar{\mathbb{D}} \) ft. to \( \bar{\mathbb{D}} \) ft. Gage \( \bar{\mathbb{D}} \) Gage	Deput dimed 200 it. Deput of completed wen === 1	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size at and show thickness and nature of each stratum with at least one entry for each change of formation of state Water Level and indicate with	n and aquifer penetrated, ion. Report each change in
(6) PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate princ  MATERIAL	From To SWL
Size of perforations in. by in.	Topsoil Topsoil	0 2
perforations fromft. toft.	Yellow Clay	2 20
perforations fromft. toft.	Large Dry Gravel	20 92
perforations fromft. toft.	Blue Clay	92 119
(E) CODERATO	Black Sand and Gravel with	
(7) SCREENS: Well screen installed? ☐ Yes 🛱 No	strips of sandy Clay	119 147
Manufacturer's Name	Blue Clay	147 284
Type Model No	Black Sand and Small gravel	284 285
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DECEMENT	
s a pump test made? X Yes No If yes, by whom? driller	RECEIVED	
Yield: 300 gal./min. with 76 ft. drawdown after 2 hrs.	0CT 2 0 1980	
" 400 " 83 • " 4 "		
500 104 6	WATER RESOURCES DEPT	
	SALEM, OREGON	
ler test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	<u> </u>	
Temperature of water Depth artesian flow encountered ft.	Work started 9/3/80 19 Complete	d 10/8/80 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10/8/80 19
Well seal—Material used Portland Cement  Well sealed from land surface to 20 ft.	Drilling Machine Operator's Certification:  This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of sealin.  Diameter of well bore below seal10	best knowledge and belief.  [Signed] Bon Martin Date 10/9/80 19  (Drilling Machine Operator)	
Number of sacks of cement used in well seal 13 sacks How was cement grout placed? poured thru tremie pipe	Drilling Machine Operator's License No. 536	
Party Party	Water Well Contractor's Certification:	
	This well was drilled under my jurisdic	ction and this report is
	true to the best of my knowledge and beli	ef.
Was a drive shoe used? X Yes I No Plugs Size: location ft.  Did any strata contain unusable water? I Yes X No	Name Willamette Drilling Co. (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 7365v O'Neil Rd. N.E. Sa	lem, Oregon 973
Method of sealing strata off	[Signed] Dollar Roce	
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contra	
Gravel placed from	Contractor's License No.561 Date	10/9/80