NOTICE TO WATER WELL CONTRACTOR WATER WELL REPORT CEIVED The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT CLAC MAR 91978 State Well No. 35/1E-34dk STATE OF OREGON SALEM, OREGON 97310 (Please type or print) within 30 days from the date 012079 (Do not write above this line) RESOURCE State Permit No. of well completion. SALEM, OREGON (1) OWNER: (10) LOCATION OF WELL: Name Jack Parsons County Clackamas Driller's well number D-97-78 25460 S.W.Baker NW 14 SE 14 Section 34 T. 3S R. Sherwood, Oregon 97140 W.M. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Deepening [Reconditioning [Abandon 🗀 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary 泅 Driven 🗆 Domestic | Industrial | Municipal | Cable Static level 50 Jetted [2-23-78 ft. below land surface. Date Dug Irrigation XXTest Well | Other Bored [Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [Welded [(12) WELL LOG: " Diam. from 0 ft. to 138 ft. Gage • 250 Diameter of well below casing .. Depth drilled 140 ft. Depth of completed well 140 " Diam. from _____ ft. to ____ ft. Gage ____ Formation: Describe color, texture, grain size and structure of materials;" Diam, from ft. to ____ ft. Gage ____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? No. | No. Type of perforator used Mills Knife MATERIAL 3/16 in by Size of perforations Top Soil 0 <u>10</u> 414 perforations from 105 ft. to 128 Cemented gravel bldrs 10 22 perforations from _____ ft. to ____ Cemented gravel 22 50 perforations from Brown clay gravel 50 62 Blue clay gravel 62 95 (7) SCREENS: Well screen installed? ☐ Yes ☐ No Gravel water 95 100 Manufacturer's Name Gravel sand water 100 127 Blue clay 127 140 Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft. Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? KYes No If yes, by whom? Driller gal./min. with 55 ft. drawdown after 4 Air Rotary Total Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. perature of water Depth artesian flow encountered _____ Work started 2-22 1978 Completed 2 - 23 19 78 (9) CONSTRUCTION: Date well drilling machine moved off of well

Well seal—Material used Cement

Well sealed from land surface to 18

Diameter of well bore to bottom of seal 12 in.

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal 11 sacks

How was cement grout placed?

 Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.

Materials used and information reported above are true to my best knowledge and belief

[Signed]

(Drilling Machine Operator's License No. 883

Water Well Contractor's Certification:

This true to th	well e be	was st of	drilled my k	l under nowled:	my jui ge and	risdiction belief.	and	this	report	i
	~ ~									

Name S & M Drilling & Supply, Inc

(Person, firm or corporation)

Address 399 S. E. Walnut/ Canby, Or 97013

[Signed]	Maci
	Vater Well Contractor)
Contractor's License No. 49	7 Date 3 - 6