NOTICE TO WATER WELL CONTRACTORY 2 1 1962 way The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date 1 and 1 11-34P(2) State Well No. State Permit No. ... Drawdown is amount water level is lowered below static level (1) OWNER: (11)WELL TESTS Name Al Delforge test made? X Yes ☐ No If yes, by whom? Address Rte 3 Box 569 100 gal./min. with 95 Yield: ft. drawdown after Canby, Oregon ,, (2) LOCATION OF WELL: Bailer test gal./min. with ft. drawdown after hrs. County Clackamus Driller's well number Artesian flow g.p.m. 1/4 Section 34 1E W.M. T. **3**S No Temperature of water Was a chemical analysis made? ☐ Yes Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing 201 Depth drilled ft. Depth of completed well Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM TO Blue clay TYPE OF WORK (check): 140 148 2

| Well Deepening Reconditioning Abandon | Danu | _148 | 150 |
|---|--|-----------------|---------------------------------------|
| andonment, describe material and procedure in Item 12. | Small gravel | 150 | 152 |
| (4) PROPOSED USE (check): (5) TYPE OF WELL: | Sandy blue clay | 152 | 175 |
| | Black sand | 175 | 199 |
| Domestic ☐ Industrial ☐ Municipal ☐ Cable ☐ Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐ | Gray clay | 199 | 201 |
| (6) CASING INSTALLED: Threaded ☐ Welded 🖾 | 44.50 | | |
| 8 "Diam, from 0 ft, to 17212" ft. Gage | 189 | | <u> </u> |
| 6 "Diam. from 161 ft. to 201 ft. Gage | | | |
| "Diam, from ft. to ft, Gage | | | · · · · · · · · · · · · · · · · · · · |
| (7) PERFORATIONS: Perforated? M Yes No | | | |
| Type of perforator used Torch | | | · · · · · |
| Size of perforations 1/8 in by 8 in. | | | |
| perforations from 17.5 ft. to 199 ft. | | | |
| perforations from ft. to ft. | | x | |
| perforations fromft. toft. | | | |
| perforations from ft. to ft. | | | |
| perforations fromft. toft. | 1,27 | | |
| (8) SCREENS: Well screen installed ☐ Yes 🛱 No | | | |
| nufacturer's Name | 11 | | |
| Model No. | | | ; |
| Slot size Set from ft. to ft. | Drilling-A | prille | 19 6 و 1 |
| Diam. Slot size Set from ft. to ft. | Work started April 5 19 62 Completed Date well drilling machine moved off of well pumpi | ng_4/3 | 19 1/63 |
| - A U1 | Date well drilling machine moved off of well Pompt | 8-J/ (| 1/192 |
| (9) CONSTRUCTION: | (13) PUMP: | | |
| Well seal—Material used in seal Bentonite Mud | Manufacturer's Name | | |
| Depth of seal | Type:H | P | |
| Diameter of well bore to bottom of sealin. | | | |
| Were any loose strata cemented off? Yes No Depth | Water Well Contractor's Certification: | | |
| Was a drive shoe used? Tyes To No | This well was drilled under my jurisdiction ar | nd this re | port is |
| Was well gravel packed? 🗌 Yes 🙀 No Size of gravel: | true to the best of my knowledge and belief. | | |
| Gravel placed fromft. toft. | NAME John Truman Miller | | |
| Did any strata contain unusable water? 🗓 Yes 🔲 XNo | (Person, firm or corporation) (Ty | pe or print) | |
| Type of water? Degin of strata | Address P O Box 42 Hubbard, Or | egon | |
| Method of sealing strata off | | | |
| (10) WATER LEVELS: | Drilling Mackine Operator's License No. 277 | *************** | |
| Static level 85 ft. below land surface Date 1/6/62 | [Signed] Water Well Contractor) | | |
| Artesian pressure , lbs. per square inch Date | Contractor's License No. 277 Date May | 22 | 10 62 |
| (USE ADDITIONAL SE | EETS IF NECESSARY) | | 10 |
| | | | |