WATER WELL REPORTED 1 1974 State Well No. 35 | 15-35 The original and first copy of this report are to be STATE OF OREGOSTATE ENGINEER filed with the (Please type or print) SALEM. OREGON State Permit No. STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (10) LOCATION OF WELL: (1) OWNER: Name Mr. Gene Cereghino County Clackens Driller's well number Address 10483 So. Township Rd. 1/4 Section 35 T. 35 R.1E Canby Oregon 97013 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning [New Well Deepening [Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Coopage Rotary 90 ft. below land surface. Date 11/1/71 Domestic | Industrial | Municipal | Cable Jetted Irrigation Test Well Other lbs. per square inch. Date Artesian pressure CASING INSTALLED: Threaded [Welded M 12 (12) **WELL LOG:** Diameter of well below casing . 12 " Diam. from 0 ft. to 275 ft. Gage 250 315 ft. Depth of completed well 315 ft. Depth drilled _______ft. Gage ________ft. Formation: Describe color, texture, grain size and structure of materials; " Diam, from _____ ft. to _____ ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? X Yes | No. Type of perforator used Four Way Drive Down MATERIAL Size of perforations 3/8 in. by 11 Top soil Clay, brown 120 perforations from ____230 ___ ft. to ____235 120 perforations from ____260 ft. to ____ Sand, packed 11 perforations from ft. to Clay, white Clay, brown (7) SCREENS: - Well screen installed? 🗌 Yes 🛣 No Clay, blue Manufacturer's Name Clay, brown Clay, gray 89 162 Diam Slot size Set from ft. to ft. Clay, brown, sandy 162 201 Diam. ____ Slot size ____ Set from ____ ft. to ____ ft. Shale. white 201 205 Clay, brown with gravel 205 230 Drawdown is amount water level is lowered below static level Bottner (8) WELL TESTS: Gravel, w.b., approx. 35gpm 230 Was a pump test made? 📆 Yes 🗆 No If yes, by whom? Drilling 239 Shale, black 259 gal./min. with 160 ft. drawdown after 16 hrs. Gravel & sand, gray W/B. 273 Rock, black, Water, brng. 298 90 Shale, black 298 gal./min. with . ft. drawdown after Bailer test tesian flow g.p.m. Work started 3/ 22/ 19 74 Completed 11/1/ mperature of water 53 Depth artesian flow encountered ft. Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used ____Cement Grout **Drilling Machine Operator's Certification:** This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to Diameter of well bore to bottom of seal 12. in. Date 11 / 22 1974 Diameter of well bore below seal Number of sacks of cement used in well seal Drilling Machine Operator's License No. 190 Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? Tes Do Plugs...... Size: location ft. Name HAAKON BOTTNER DRILLING COMPANY Did any strata contain unusable water? 🛘 Yes 🏖 No (Person, firm or corporation) Address 3424 S.E. 174th., PORTIAND, ORE. 97236 Type of water? Method of sealing strata off Was well gravel packed? ☐ Yes 🔼 No Size of gravel: ... Contractor's License No. 109 Date 11 / 22 / , 19 74

NOTICE TO WATER WELL CONTRACTOR

MEGEIVE