CLAC

3/1-35

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE OF OREGON

State Well No. ...

(1) OWNER:	(11) WELL TESTS: Drawdown is amount w lowered below static lev	ater level is	
Name Emil Kraft	Was a pump test made? Yes No If yes, by Runno		20we
Address Canby, Ore.	Yield: 340 gal./min. with 131 ft. drawdown		A
	" 280 " 111 "	3/1	,,
(O) YOU AMONG ON TWEET	" 210 " 88 "	3/4	,,
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown	-, .	hrs.
County Clackamas Owner's number, if any—	Artesian flow g.p.m. Date		
½ ½ Section 35 T. 3S R. TE W.M.	Temperature of water 52 Was a chemical analysis ma	de? 🏻 Yes	X No
Bearing and distance from section or subdivision corner			
	(12) WELL LOG: Diameter of well		inches.
	Depth drilled 257 ft. Depth of completed we	ell 257	ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	l and structur he material i	re, and n each nation.
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	Brown sandy clay	0 22	,
New Well Deepening ☐ Reconditioning ☐ Abandon ☐	Cement gravel & boulders		47
bandonment, describe material and procedure in Item 11.	Yellow clay silt&gravel	47 55	
	Yellow sand&silt	55 68	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Cemented gravel	68 94	
Domestic Industrial Municipal Rotary Driven	Blue clav	9h 17	
Irrigation → Test Well □ Other □ Dug → Bored □			
Dug St. Borett	Grey clay	175 19	
(6) CASING INSTALLED: Threaded Welded	Blue clay	198 20	и
10" Diam. from6 ft. to236 ft. Gage atd	Gray sandy clay	207216	
6" Diam. from221ft. to257ft. Gage 250	Gray silt	216 24	
	Gray packed sand (water)	<u>2L3 25</u>	
27 00 100 100 100 100 100 100 100 100 100	Gray clay	255 25	<u>27 </u>
(7) PERFORATIONS: Perforated? 🙀 Yes 🗆 No			
Type of perforator used Torch			
SIZE of perforations 1/8 in. by 12 in.			
66 perforations from 227 ft. to 253 ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed ☐ Yes ↓ No			
Manufacturer's Name			
<u>Type</u> Model No,			
n Slot size Set from ft, to ft.			
Slot size Set from ft. to ft.	Work started 77/7/67 19 . Completed 7	120 160	19
	14/1901	130/06	
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? Yes No Size of gravel:3/8	Manufacturer's Name	*******************************	
Gravel placed from227	Type: H.P.		
Was a surface seal provided? 🛣 Yes 🗌 No To what depth?30 ft.			·····
Material used in seal— drill cuttings	Well Driller's Statement:		
Did any strata contain unusable water?	This well was drilled under my jurisdiction at	nd this repo	ort is
Type of water? Depth of strata	true to the best of my knowledge and belief.		
Method of sealing strata off	NAME Steinman Bros. (Person, firm, or corporation) (Typerson)	***************	
(10) WATER LEVELS:	(Person, firm, or corporation) (Type	pe or print)	
Static level 71, ft. below land surface Date 7/20/62	Address 15112 S.E. McLoughlin , Mil	waukie C	re.
Artesian pressure lbs. per square inch Date	Driller's well number962		
Log Accepted by:	[Signed] Slinman Bas)	£	
[Signed] [Smill Araft Date Feb. 7 , 1962			
(Owner)	License No Date2/7/		9