


NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.



WATER WELL REPORT

RECEIVED

MAY 6 1968

State Well No. 3/1-35 C

(Please type or print)

(Do not write above this line)

STATE ENGINEER SALEM OREGON

State Permit No.

(1) OWNER:

Name Al Delferge Address Rte 1 Box 404 Canby, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [x] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

8.0" Diam. from 0 ft. to 197 ft. Gage 1/4"

(6) PERFORATIONS:

Perforated? [] Yes [x] No. Type of perforator used. Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No. Manufacturer's Name. Type. Model No. Diam. Slot size. Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 102 ft. below land surface Date 5/2/68. Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [x] Yes [] No. If yes, by whom? driller. 150 gal./min. with 5 ft. drawdown after 1 hrs. Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date. Temperature of water. Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal-Material used Puddled mud. Depth of seal 24 ft. Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? [] Yes [x] No. Depth. Was a drive shoe used? [] Yes [x] No. Did any strata contain unusable water? [] Yes [x] No. Type of water? depth of strata. Method of sealing strata off. Was well gravel packed? [] Yes [x] No. Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Clackamas Driller's well number 1/4 1/4 Section 35 T. 3S R. 1E W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 8. Depth drilled 246 ft. Depth of completed well 246 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Brown sandy clay, Cement gravel, Blue sandy clay, Blue clay, Green sandy clay, Blue clay, Sand, Blue sandy clay, Basalt rock, Blue shale rock, Brown rock, Black basalt.

Work started April 15 1968 Completed May 2 1968. Date well drilling machine moved off of well May 2 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John T. Miller Date May 4, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 26

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller (Person, firm or corporation) (Type or print) Address P. O. Box 342 Hubbard, Oregon [Signed] John T. Miller (Water Well Contractor) Contractor's License No. 277 Date May 4, 1968