## WATER WELL REPORT STATE OF OREGON

CLAC

912432

## RECEIVED

APR 16 1981 State Well No.

45/1E-23/24

WATER RESOURCES DERTPermit No. SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name LYNN KRAXBERGER	County CLACKAMAS Driller's well	number 3-15-81	
Address 10227 MACKSBURG ROAD	· NE ¼ NW ¼ Section 23 T. 4S	R. 1E W.M.	
City CANBY State OREGON	Tax Lot # 00700 Lot Blk	Subdivision	
(2) TYPE OF WORK (check): 97013	Address at well location: Same	·	
	·		
New Well   Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed w	ell.	
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found	11 #	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 55 ft. below land surface. Date 4-3-81		
Rotary Air Driven Domestic D Industrial Municipal D	Artesian pressure lbs. per square inch. Date		
Rotary Mud 🗆 Dug 🗆 Irrigation 🐧 Test Well 🗆 Other 🖂			
Ä Bored □ Thermal: Withdrawal □ Reinjection □		casing8	
(5) CASING INSTALLED: Steel  Plastic  Threaded  Welded	Depth drilled 193 ft. Depth of Formation: Describe color, texture, grain size and stru	completed well 193 ft.	
	thickness and nature of each stratum and aquifer pene	trated, with at least one entry	
8."Diam. from0 ft. to163 ft. Gauge250	for each change of formation. Report each change in p and indicate principal water-bearing strata.	osition of Static Water Level	
"Diam. from		<del></del>	
LINER INSTALLED:	MATERIAL	From To SWL	
7 "Diam from 153 ft. to 193 ft. Gauge .188	TOP SOIL	0 2	
(6) PERFORATIONS: Perforated? Yes  No	CLAY BROWN	2 29	
Type of perforator used Cutting torch	GRAVEL SAND BROWN	29 52	
Size of perforations 4 in. by 8 in.	CLAY BROWN SAND FINE	52 67	
60 perforations from 170 ft. to 186 ft.	GRAVEL SAND BROWN	67 87	
perforations fromft. toft.	CLAY BROWN SAND FINE	87   106	
perforations fromft. toft.	CLAY BLUE SAND BLACK	106 112	
V	SANDSTONE BROWN	112 122	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	CLAY GRAY SAND BLACK FINE	122   133	
Manufacturer's Name	SAND BLACK FINE	133   150	
Type Model No.	CLAY GRAY SAND BLACK FINE	150 163	
Diam. Slot Size	CLAY BLUE SAND BLACK	163 171	
Diam. Slot Size Set from ft. to ft.	SANDSTONE BLACK	171 186 55	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CLAY GRAY	186 193	
When a pump test made? ☐ Yes 💆 No If yes, by whom?	· · · · · · · · · · · · · · · · · · ·		
d: gal/min. with ft. drawdown after hrs.			
** 1			
Air test gal/min. with drill stem at ft. hrs.  Bailer test 40 gal/min, with 20 ft. drawdown after 2 hrs.			
Bulling Han 20 Carlotte 1200			
g.p.m.  Separature of water  Depth artesian flow encountered ft.			
	Work started 3-18 19 81 Complete		
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well	4-3 19 81	
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my directs:	upervision. Materials used	
Diameter of well bore to bottom of seal 12in.	and information reported above are true to the		
Diameter of well bore below seal	(Drilling Machine Operator)	Date 7	
Number of sacks of cement used in well seal 26 sacks	Drilling Machine Operator's License No	)38	
How was cement grout placed? pressure grouted	Water Wall Control of the Control of		
E. C.	Water Well Contractor's Certification:		
VI	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was pump installed?	Name BARNETT DRILLING 1 PUNKS		
Was a drive shoe used?  Yes  No Plugs	(Person, firm or corporation)	MIL DE	
Type of Water? depth of strata	Address 7101 SE C1712633	WILL DEC	
Method of sealing strata off	[Signed] Dan W. Dun	en.	
Was well gravel packed? ☐ Yes 💢 No Size of gravel:	(Water Well Contract	F. 14	
Gravel placed from	Contractor's License No	ļ.~, 19&J	