

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

CLACK WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

12499

STATE OF OREGON

(Please type or print)

MAR 24 1978

State Well No. 4S/1E-24ba

State Permit No.

(Do not write above this line)

WATER RESOURCES DEPT.

(1) OWNER:

Name Rufus Kraxberger
Address 11320 S Macksburg Rd
Canby, Oregon 97013

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 190 ft. Gage # 250
6 9/16" Diam. from 190 ft. to 208 ft. Gage # 188

(6) PERFORATIONS:

Perforated? [] Yes [X] No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [X] Yes [] No

Manufacturer's Name Johnson
Type Low carbon steel Model No.
Diam. 8 tel Slot size .30 Set from 180 ft. to 238 ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? Aqua pump
Yield: 225 gal./min. with 90 ft. drawdown after 14 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? poured

Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number D-101-78
NE 1/4 NW 1/4 Section 24 T. 4S R. 1E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 90 ft.
Static level 70 ft. below land surface. Date 3/6/78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 240 ft. Depth of completed well 238 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Clay, brn, Cemented gravel, Clay, Brn, Clay blue, Gravel & sand wtr brng, Clay blue, Sand blk, wtr brng, Clay blue.

Work started 2-28 19 78 Completed 3-6 19 78
Date well drilling machine moved off of well 3-6 19 78

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Brian Blocker Date 3-13, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1169

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name S & M Drilling & Supply Inc
(Person, firm or corporation) (Type or print)

Address 399 S.E. Walnut / Canby, Or 97013

[Signed] Water Well Contractor

Contractor's License No. 497 Date 3-15, 19 78