NOTICE TO WATER WELL CONTRACTOR.
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Ray Sherrill	County Clackanes Driller's well number		
Address Rt. 2, Box 308	NE 14 SW 14 Section 27 T. 45 R. 1E W.M.		
Canby, Oregon 97013	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):	Dearing and allowed		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	CALL THE PROPERTY CONTRACTOR	_11	
	(11) WATER LEVEL: Completed we	211.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 97		ft.
Rotary Driven Domestic Industrial Municipal	Static level 32 ft. below land st	urface.Date 6/	<u>/9/73</u>
Cable	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing	8
.8	Depth drilled 154 ft. Depth of completed well 154 ft.		
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a	<u></u>	
ft. Gageft.	and show thickness and nature of each stratun	n and aquifer pen	etrated,
	with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report each ch	iange in
PERFORATIONS: Perforated? Yes No.		· · · · · · · · · · · · · · · · · · ·	
Type of perforator used Mills knife	MATERIAL	From To	SWL
Size of perforations 1/2 in. by 3 in.	Top soil	0 . 5	
110 perforations from 108 ft. to 126 ft.	Clay, brown	2 16	
perforations from	Sand, brown	16 29	
perforations fromft. toft.	Clay, blue	29 39	
(7) SCPEENS.	Sand & gravel, brown	39 68	
(7) SCREENS: Well screen installed? Yes No	Sand, brown	68 71	
Manufacturer's Name	Gravel	71 75	
TypeModel No.	Clay, brown	75 93	
Diam. Slot size Set from ft. to ft.	Gravel, brown, med.	93 131	32
Diam, Slot size Set from ft. to ft.	Clay, brown to grey	131 147	20
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand & gravel, black Clay, blue	147 154 154	<u> </u>
Was a pump test made? TYes XNo If yes, by whom?			
Yield: gal./min. with it drawdown after hrs.	The second section of the sect		_
" " " "			
<u>" 60 " 14 " 1 "</u>			
Bailer test gal./min. with ft. drawdown after hrs.	<u> </u>		
Artesian flow g.p.m.			
perature of water 52 Depth artesian flow encountered ft.	Work started 6/5 19 73 Complete	ed 6/13	1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u>6/13</u>	19 73
Well seal-Material used Bentonite & puddled clay	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my Materials used and information reported	above are true	ision.
Diameter of well bore to bottom of sealin.	best knowledge and belief	asove and made	10 111,
Diameter of well bore below seal8 in.	[Signed]	Date 6/15,	197.3
Number of sacks of cement used in well seal	(Drilling Machine Operator)	527	, ,
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	<u> </u>	iction and this	mort is
of waterlbs./100 gals.	This well was drilled under my jurisdi true to the best of my knowledge and bel	ief.	กัการ หล
Was a drive shoe used? Yes No Plugs Size: location ft.	Name C. G. Westerberg		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print	
Type of water? depth of strata	Address Rt. 1 Box 151, M	ulino, Ore	g.on.
Method of sealing strata off	[Signed] Contractions		
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contr	/ /	
Gravel placed fromft. toft.	Contractor's License No86 Date	6/15	, 19.73