

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion

RECEIVED DEC 30 1969 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

CLAC

12567

4/1-27ca

State Well No.

State Permit No.

G 5159

(1) OWNER:

Name DAVE BROWN Address Rt 2 Box 311 Canby, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [x] Test Well [ ] Other [ ]

CASING INSTALLED:

Threaded [ ] Welded [x]

10" Diam. from 7.1 ft. to 168 ft. Gage 250

PERFORATIONS:

Perforated? [ ] Yes [x] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 40 ft. below land surface Date 12/6/69

Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [ ] No If yes, by whom? DRILLER

Yield: 200 gal./min. with 110 ft. drawdown after 6 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 54° Was a chemical analysis made? [ ] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used BENTONITE CLAY & DRILL CUTTINGS

Depth of seal 30 ft.

Diameter of well bore to bottom of seal 14 in.

Were any loose strata cemented off? [ ] Yes [x] No Depth

Was a drive shoe used? [x] Yes [ ] No

Did any strata contain unusable water? [ ] Yes [x] No

Type of water? depth strata

Method of sealing strata off

Was well gravel packed? [ ] Yes [x] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County CLACKAMAS Driller's well number 16 1/4 Section 27 T. 45 R. 1E W.M.

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 170 ft. Depth of completed well 170 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include TOP SOIL, GRAY CLAY, CEMENT GRAVEL, LOOSE GRAVEL, YELLOW CLAY, GRAVEL, BROWN SAND, BLUE CLAY, SAND + GRAVEL, BLUE CLAY, GRAY SAND, BROWN CLAY, BLUE CLAY, GRAY SAND.

Work started 11/25 1969 Completed 12/6 1969

Date well drilling machine moved off of well 12/6 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] J. J. Swell Date 12/6, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 179

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME William D. Christenson, Jr. (Person, firm or corporation) (Type or print)

Address P.O. Box 343 Hubbard, Ore

[Signed] William D. Christenson (Water Well Contractor)

Contractor's License No. 511 Date 12/6, 1969