	L REPORTECEIVED	45/1E-29 bb
WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 Within 30 days from the date (Rlease type	or print) AUG 3 1981).
of well completion. (Do not write ab	ove thank ER RESOURCES DEPT	
	BALEM, ORLGON	
(1) OWNER:	(10) LOCATION OF WELL:	. 102
Name Jim Markin	County Clackamas Driller's well nu	mber 192
Address 28198 S. Barlow Rd.	NW 14 NW 14 Section 29 T. 4S	R. 1E W.M.
Aurora, Or. 97002	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):		
New Well 🔣 Deepening 🗌 Reconditioning 🗋 Abandon 🗍		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	84 ft.
Rotary K Driven Domestic Industrial Municipal	Static level 45 ft. below land s	urface. Date 7-27-81
Cable	Artesian pressure lbs. per squar	•
Dug	Artesian pressure ibs. per squar	e men. Date
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well b	elow casing 811
8 " Diam. from 0 ft. to 104 ft. Gage • 250 7 0 . D . " Diam. from 95 ft. to 155 ft. Gage • 188	Depth drilled 155 ft. Depth of compl	4
7 O.D." Diam. from 95 ft. to 155 ft. Gage . 188		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain fize and show thickness and nature of each stratu	
	with at least one entry for each change of forma	tion. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipai water-bearing strata.
Type of perforator used Korch	MATERIAL	From To SWL
Size of perforations $\frac{1}{4}$ in. by 8 in.	Top soil	0 2
54 perforations from 105 ft. to 155 ft.	Clay, brown	2 22
perforations fromft. toft.	Clay, sand, brown, med.	22 45
perforations from ft. to ft.	Clay, sand, blue, fine	45 54
	Gravel, sand, compact, br.	54 80
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Clay, sand, blue, black, fn	80 84
Manufacturer's Name	*Gravel, sand, black, med.	84 93
Type Model No.	Clay, sand, black, fine	93 104 104 104 153
Diam. Slot size Set from ft, to ft.	*Sandstone, black	104 153 153 155
Diam, Slot size Set from ft. to ft.	CCay, blue	2.00
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Nes Do If yes, by whom? Driller		
•		
Bullyman Will C V 20 did Will Color		
" "	who have the	
11 11 11 11 11 11 11 11 11 11 11 11 11	F 1 1 1	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	-	
perature of water Depth artesian flow encountered ft.	Work started 7-23 19 81 Complet	ed 7–27 1981
	Date well drilling machine moved off of well	7-27 1981
(9) CONSTRUCTION:		
Well seal—Material used Cement	Drilling Machine Operator's Certification: This well was constructed under my	
Well sealed from land surface to 20 ft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	7 00 01
Diameter of well bore below seal8 in.	(Drilling Machine Operator)	Date 7-29, 1981
Number of sacks of cement used in well seal 18 sacks How was cement grout placed? Pressure grouted from	Drilling Machine Operator's License No.	994
How was cement grout placed? I I Common Surface.		
20 11. 00 18/10 801 1003	Water Well Contractor's Certification:	
The second secon	This well was drilled under my jurisd	
Was a drive shoe used? Z Yes 🗆 No Plugs Size: location ft.	true to the best of my knowledge and be	
Did any strata contain unusable water? Tyes No	Name B & G Drilli (Person, firm or corporation)	(Type or print)
	Address 10030 S. Macksburg F	
Type of water? depth of strata		Dall
Method of sealing strata off	[Signed] Alorgo Warner	
Was well gravel packed? Yes No Size of gravel:	(Water wen cont	
Gravel placed fromft. toft.	Contractor's License No. 637 Date	7-29 , 19.83