NOTICE TO WATER WELL CONTR

WATER WELL REPORT

G-3823

012649 State Well No.

State Permit No.

The original and first copy of this report are to be filed with the STATE ENGINEER WELL REPORT OF OREGON WITHIN 30 days from the date 1 LEM OREGON (Please type or print) of well completion.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static lev	vater level vel	is
Name ELI LILLY & COMPANY SIP 46206	Was a pump test made? Wes \(\square\) No If yes, by whom	17 DRII	LER
Address P.O. BOX 814 INDIANAPOLIS, INDIANA DR. CHAMBERIAIN 14819 S.E. PRIMROSE	Yield: 30 gal./min. with IOOft. drawdow	n after (3 hrs.
AN LOCATION OF WHAT MITWATKEE OPERON	n n		"
(2) LOCATION OF WELL: MILWAUKIE, OREGON	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County CLACKAMAS Driller's well number II94	Artesian flow g.p.m. Date	7722 4234	
34 34 Section 29 T. 4S R. IK W.M.	Temperature of water Was a chemical analysis n	nađe? □ Y	es 🗆 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below case	А	
* **	TEO	TEA	
	Depth drilled 159 ft. Depth of completed well		ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	, and struc he materia lange of fo	ture, and Il in each ormation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	TOP SOIL	0	3
Vew Well Comparison □ Reconditioning □ Abandon □	YELLOW CLAY	3	IO
andonment, describe material and procedure in Item 12.	CEMENT GRAVEL & SMALL BOULDE		22
(4) PROPOSED USE (check): (5) TYPE OF WELL:	STICKY GRAY SHALE	22	40
Potenty Cl. Driven Cl.	BROWN SHALE	40	45
Cable A Jetted	BROWN SAND & SOME SOME SHALE	45	<u>55</u>
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	BLUE SHALE SOFT	55	65
(6) CASING INSTALLED: Threaded □ Welded \(\frac{\frac{1}{2}}{2}\)	BROWN SHALE	65	70
"Diam. fromft. toft. Gage	BROWN SHALE & SAND	70	83
8 Diam from TOP ft to I45 ft Gage 250	FINE BROWN SAND	83	95
"Diam. fromft. toft. Gage	BROWN SHALE	95	II5
	BROWN SAND & SOME MUD	II5	I30
(7) PERFORATIONS: Perforated? Yes No	BROWN SHALE	I30	I3 8
Type of perforator used	BLUE SHALE	<u>I</u> 38	I50
Size of perforations in. by in.	BLACK SAND	<u> 150</u>	<u>I5</u>
perforations from ft. to ft.	BLACK PEAT	I54	<u> 159</u>
perforations from ft. to ft.	BLUE SHALE CRUMBLY	I59	. ?
perforations from ft. to ft.	8-T-14-T-17-17-18-18-18-18-18-18-18-18-18-18-18-18-18-		
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? Yes XNo		1	
Manufacturer's Name			
Model No.			
Slot size Set from ft. to ft.	Work started DEC 29 1966 Completed JA	N I9	<u> 1967</u>
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well JAN	I 9 I9	6719
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal CEMENT & PUDDLE CLAY	Manufacturer's Name		
Depth of sealft. Was a packer used?	Type:		
Diameter of well bore to bottom of sealin.	YYLA YII YI CAALA AAA CAALA AA		
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? X Yes \(\subseteq No \)	This well was drilled under my jurisdiction a	and this r	report is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		-
Gravel placed from ft. to ft.	NAME WILLAMETTE DRILLING CO.		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, O	REGON	
Method of sealing strata off	Drilling Machine Operator's License No. 74	•	
(10) WATER LEVELS:	O SO O O		***********
Static level 45 ft. below land surface Date I/I9/67	[Signed] (Water Well Contractor)	******************	
Artesian pressure lbs. per square inch Date	Contractor's License No Date JAN I	9 I96	6 19

(USE ADDITIONAL SHEETS IF NECESSARY)