NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to filed with the

WATER WELL REPORT (Please type or print (Do not write above this ine)

State Well No

STATE ENGINEER, SALEM, OF within 30 days from the date of well completion STATE ENGINEER

01288 Permit No.

(1) OWNER: SALEM OREGON	(11) LOCATION OF WELL: County Clackamas Driller's well number		
Name Mr. and Mrs. W. T. McCoy			
Address Rt. 1, Box 258, Sandy, Oregon	14 . 14 Section 35 T. 1S		W.M.
	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):	bouring and distance from Section of Superinter	- COLLICE	
New Well 🔣 Deepening 🗌 Reconditioning 🗍 Abandon 🗀	%		
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOC.		
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal Domestic D	(12) WELL LOG: Diameter of well below casing—9———		
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Depth drilled 398 ft. Depth of comple	eted well	398 ft.
CASING INSTALLED: Threaded Welded W. 8." Diam. from 0. ft. to 399 ft. Gage 277	Formation: Describe color, texture, grain size and show thickness and nature of each stratum with at least one entry for each change of form in position of Static Water Level as drilling pro	m and aquife ation. Report	er penetrated, t each change
" Diam. from ft. to ft. Gage	MATERIAL		To SWL
ft. Gage	Top soil	0	7
PERFORATIONS: Perforated? W yes No.	Yellow clay	Ť	12
	Gritty clay & boulders	12	74
Type of perforator used Drive down	Gravel & cobbles	7),	83
Size of perforations 5/16 in. by 1 in.	Pink gray rock	83	92
	Geay Fock		.03
	Boulders, cobbles & gra-	103 7	.69
_105 perforations from _382 ft. to _389 ft.	Rock, gray		69
perforations from ft. to ft.	Sandy clay		74
perforations from	Brown & Yellow sand rock	174 2	109
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Boulders	209 2	15
Manufacturer's Name	Gravel	215 2	25
Type Model No.	Gray sandrock		40
Diam. Slot size Set from ft. to ft.	Hard sandy clay		18
Diam. Slot size from ft. to ft.	Silt & clay		22
(8) WATER LEVEL: Completed well.	Sand & gravel - water		29 285
tt. below land surface Date 4-11-68	Silt, hard	320 3 356 3	50
	Gravel & sand -water Blue & brown sandy silts		29 275
Lesian pressure lbs. per square inch Date	Blue gray coarse sand		82
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	Brown silt & black sand		84 90 300
Was a pump test made? XYes No If yes, by whom! Driller	Brown Silt & blue clay		98
gal./min. with 60 ft. drawdown after 7 hrs.	Work started 1-23 1968 Complete	ed 1, -1	
gar, min. with OO it. drawdown after hirs.	Date well drilling machine moved off of well	4-12-6	
A STATE OF THE STA		<u> </u>	
	Drilling Machine Operator's Certification: This well was constructed under my di	raat aunami	sion Mata
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported abov	e are true	to my best
Artesian flow g.p.m. Date	knowledge and belief:		-
Temperature of water 530 Was a chemical analysis made? ☐ Yes ØNo	[Signed] Janua & Street	Date 5-	12., 1968
(10) CONSTRUCTION:	Drilling Machine Operator's License No	18	
Well seal—Material used Cement			
Depth of seal 135	Water Well Contractor's Certification:		
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Were any loose strata cemented off? Yes No Depth			
Was a drive shoe used? XYes No	NAME Calvin C Brom Well Drilling		
Did any strata contain unusable water? 💆 Yes 🕱 No	Address 17120 S. E. Foster F	ld. Par	rt.len <i>d</i>
Type of water? depth of strata		Oreg	
Method of sealing strata off	[Signed] Salmer CA	Sum	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contract	ior)	
Gravel placed fromft. toft.	Contractor's License No. 222 Date	5-12	1968