The original and first copy of this report are to be filed with the STATE OF OREGON JUN 3 1974 State Well No. STATE ENGINEER, SALEM, OREGONTABE ENGINEER (Please type or print) STATE ENGINEER SALEM, OREGON OREGON OREGON OREGON SALEM. OREGON OREGON SALEM. OREGON SALEM. OREGON SALEM. OREGON SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name Charles Dietz	County Clackamas Driller's well no	ımber		
Address Rte 1 Box 398 Canby, Oregon 97013	14 14 Section 2 T. 4S	R. 1F	E	W.M.
	Bearing and distance from section or subdivisi	on corner	:	
(2) TYPE OF WORK (check):				
New Well 🖾 Deepening 🗌 Reconditioning 🗋 Abandon 🔲				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		61		ft.
Rotary Driven Domestic Industrial Municipal	Static level 52 ft. below land s	urface.	Date 5/	29/74
Cable	Artesian pressure lbs. per squar			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	,	_	Ω
8." Diam from 0 ft to 171 ft Gage 14"				
	Depth drilled 175 ft. Depth of compl	eted well	175	ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu			
	with at least one entry for each change of forma	tion. Repo	rt each	change in
Perforated? Yes No.	position of Static Water Level and indicate prin	cipal wat	er-beari	ıg strata.
Type of perforator used	MATERIAL	From	то	swr-
Size of perforations in. by in.	Top soil	0	3	Q
perforations from ft. to ft.	Brown clay	3	61	
perforations from ft. to ft.	Cement gravel	61	97	26
perforations fromft. toft.	Blue clay	97	709	
	Sand & gravel	100	123	47
(7) SCREENS: Well screen installed? ☐ Yes 🙀 No	Grey clay	123	171	
Manufacturer's Name	Sand & gravel	171	175	
Type Model No.	,			
Diam Slot size				<u> </u>
Diam. Slot size from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	127			
Was a pump test made? 🛨 Yes 🗆 No If yes, by whom? driller				
Yield: 200 gal./min. with 53 ft. drawdown after 24 hrs.				
" " "		1		
" " " "		<u> </u>		
	. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	 		
	· · · · · · · · · · · · · · · · · · ·	├		
Artesian flow g.p.m.	1 111	<u> </u>		<u> </u>
erature of water Depth artesian flow encountered ft.	Work started April 27 1974 Complete		7 29	19 74
(9) CONSTRUCTION:	Date well drilling machine moved off of well	May	7 29	19 74
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported			
Diameter of well bore to bottom of sealin.	best knowledge and belief			
Diameter of well bore below seal	[Signed] (Driving Machine Operator)	Date ME	y29.	., 19.74.
Number of sacks of cement used in well seal 47 sacks	Drilling Machine Operator's License No.	26		
Number of sacks of bentonite used in well seal sacks	Driffing Machine Operator's License No.			***************************************
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction an	d thic r	enort is
of water lbs./100 gals.	true to the best of my knowledge and bel		~ min i	CPOL 12
Was a drive shoe used? ■ Yes □ No Plugs Size: location ft. Did any strata contain unusable water? □ Yes ▼ No	Name John Truman Miller (Type or print)			
Type of water? depth of strata	Address P O Box 341 Hubbard, Oregon 97032			
Method of sealing strata off	[Signed] John J. Mill			
Was well gravel packed? ☐ Yes 💽 No Size of gravel:	(Water Well Contr			
Gravel placed fromft_toft.	Contractor's License No277. Date]	4ay29)m	<u>, 197</u> 4
# T				