## STATE OF OREGON

AUG 27 1987

45/1E-82x

9809C 10/85

## WATER WELL REPORT (as required by ORS 537.765)

	WELL REPO ed by ORS 537.765			WATER RESOURCES DEPT. SALEM, OREGON				
(1) OWNE	R:	Owner's Well N	Tumber:	(9) LOCATION OF WELL by I	egal d	escrin	tion:	
Name 375	MICES			County Clacicama Stitude				,
	85 S. LOW	E ELDER RO						
City CANBY State OR Zip 97013				Township 45 For S, Range E or F, WM.  Section 8 45 4 56 4				
(2) <b>TYPE</b>	OF WORK:	-		Tax Lot Block			iriaian	
New Well		Recondition	Abandon	Street Address of Well (or nearest address)			ivision	•
	METHOD:			- Control of Well (of Healest address)				
Rotary Air	Rotary Mud	☐ Cable ☐	Other	(10) STATIC WATER LEVIS				
indiany An	i Rotary iviud	∟ Cable ∟	Other	(10) STATIC WATER LEVEL	:		4	
				ft. below land surface.			Aug	5,198
(4) <b>DDOD</b>	OSED USE:			Artesian pressurelb. per s	quare inc	h. Date		
omestic		Industrial Ir	rigation	(11) WELL LOG: Ground elevati	on			
Thermal		Other	rigation	Material	From	То	WB?	SWL
				TOPSOIL SANDY	FIOII	<del></del>	WD:	SWL
(5) BORE HOLE CONSTRUCTION:  Depth of Completed Well			1 1 73	3	3			
_	=	al Standards date of app		CLAY GERY	8	15	<u></u>	
HOLE	t	SEAL	Amount	CEMENTED GRAVEL & CORBLES		23		
Diameter From			sacks or pounds	CLAY GREY	53	58		<del>                                     </del>
8 20		1761 20		CLAY BLUE GREEN	2.8	73		
_ <u> </u>	185	-		CLAY GREEN SAND STREAM		78	~	
				CLAY GREY	78	85		<b></b>
77	10.26.1 1 🗍	·		GREEN CLAY SANS LAYERS	85	95		
How was seal place	ed? Method LA	BENTONITE	⊔ E na r~u co>	GREEN CLAY	95	110		
				CLAY GREEN MED, SANDLAVERS		116		
	om ft. to n ft. to			GREY CLAY THOWING SILTY		145		
		ft. Size of grave	74 1111043	SAND BLACK	145	158	-	
(6) CASING/LINER:  Diameter From To Gauge Steel Plastic Welded Threaded			CLAY BLUE	158	182			
Casing:		#250 P	Welded Threaded		182	185		
Casing.	¥ . 72							<del></del>
Liner:	140 148	188 1						
<u> </u>	153 158	.188	<u> </u>	:				
Final location of sl	hoe(s) <u>145</u>	-						
(7) PERFO	RATIONS/SO	CREENS:						
Perforat		= "						
Screens		ELL STRAINERNater	SMUVESS					
E Screens	Slot Co	rele/pipe						
From To	size Number	Diameter_ size	Casing Liner					
148 15	3 30	8					-	
		<b>3</b>				,		
		· ±	🖳 💮 🗀			-		
		**		Date started July 28 Comm		1 -	- ,	
			Ц	Comp		Jug5	1987	
(8) WELL'	TESTS: Minin	num testing time	s 1 hour Flowing	(unbonded) Water Well Constructor Cer				
☐ Pump	☐ Bailer	Air	Artesian	I constructed this well in compliance standards. Materials used and information re	with O	regon w	ell const	ruction
Yield gal/min	Pumping level	Drill stem at	Time	knowledge and belief.	ported a	bove are	true to 1	my best
200		105	½ hr		_			
180		105'	1 hr	Signed		Date		
160		105'	2hR	(bonded) Water Well Constructor Certif	ication			
				I accept responsibility for construction	of this	well and	its com	nliance
remperature of wa		Depth Artesian Flor	v Found	with all Oregon water well standards. This	report is	true to	the best	of my
Was a water analys		By whom	11	knowledge and belief.	a			-
		e for intended use? To	oo little	Signed Keeland & Seele	/ - Do	te <i>As</i>	14.5	347
	ldy 🗌 Odor 🔲 Ço	· <del>-</del> ·		10	Da	~ <del>~ ~ ~</del> /.	17	10/
⊃eptn of strata:				Company DECK WELL DRILLIN	K_Co	. Job No.		