NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

CLAG 013309

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 4s/1E-18b
State Permit No.

(1) OWNER:
Name Steve Bosch
Address Rt. 3 Box 558
Aurora, Oregon 97002

(2) TYPE OF WORK (check):
New Well XX Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary XX Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation XX Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded XX
8" Diam. from 0 ft. to 95 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes XX No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? XX Yes ☐ No
Manufacturer's Name Johnson
Type Stainless steel tele Model No.
Diam. Slot size Set from ft. to ft.
Diam. 8 Slot size 10.0 Set from 94 ft. to 99 ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? XX Yes ☐ No If yes, by whom? driller
Yield: 60 gal./min. with 15 ft. drawdown after 13 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? pressure grouted
Was a drive shoe used? XX Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes XX No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes XX No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number D288-80
NW ¼ ¼ Section 18 T. 4 R. 1 W.M.
Bearing and distance from section or subdivision corner
Meridian Road

(11) WATER LEVEL: Completed well.
Depth at which water was first found 68 ft.
Static level 50 ft. below land surface. Date 3/17/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8
Depth drilled 103 ft. Depth of completed well 99 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
topsoil	0	2	
clay sandy brown	2	68	
gravel & sand water/bear	68	103	50

RECEIVED
APR 30 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started March 13 1980 Completed March 18 1980
Date well drilling machine moved off of well 3/20/80 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Brian Baker (Drilling Machine Operator) Date 3/18/80, 19
Drilling Machine Operator's License No. 1169

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name [redacted] (Person, firm or corporation) (Type or print)
Address S & M Drilling 399 SE Walnut Canby, Ore 97013
[Signed] [signature] (Water Well Contractor)
Contractor's License No. 497 Date 3/18/80, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119