NOTIGE TO WATER WELL CONTRACTOR
The original and first copy of this report L A C
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date

STATE OF OREGON

State Well No.	4/5	18-	18
----------------	-----	-----	----

of well completion.

013310 (Piease Joseph Con not write above this line)

State	Well No. 45/18-18
Ctoto	Tlammit No.

(1) OWNER:	(10) LOCATION OF WELL:	20.	
Name ERRIC KOSS	County (LACKAMAS Driller's well n	umber 380	0
Address 26851 5 BARLOW RD		R. IE	W.M.
CANBY CREGON	Bearing and distance from section or subdivisi	ion corner	
(2) TYPE OF WORK (check):	i		
New Well □ Deepening ■ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		30	a aft.
Rotary Driven Domestic Dindustrial Municipal	Static level 64 ft. below land		17/70
Cable B Jetted D Irrigation K Test Well Dother			
	Attestati pressure ins. per squar	re inch. Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	helow cosing	
6 "Diam from 120 ft. to 128 ft. Gage 250	Depth drilled 240 ft. Depth of compl		3 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size		
	and show thickness and nature of each stratu	ım and aquifer p	enetrated.
PERFORATIONS: Perforated? Yes Wo	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each acipal water-beari	change in
Type of perforator used	MATERIAL	7	
Size of perforations in. by in.	BLUE CLAY	From To	SWL
	SOFT SANDSTONE	134 228	11
perforations from ft. to ft.	LOOSE COARSE SAND	232 231	24
perforations from	SOFT SANDSTONE	730 237	24
	BLUE CLAY	237 240	
(7) SCREENS: Well screen installed? X Yes \(\square\) No			
Manufacturer's Name OOHNSON			
Type Model No.			
Diam. 6 Slot size 25 Set from 228 ft. to 238 ft.			
Diam. Slot size Set from ft. to ft.	-		
(8) WELL TESTS: Drawdown is amount water level is		<u> </u>	
lowered below static level	ACCEIVED	ļ	·
Was a pump test made? Yes No If yes, by whom?	OCT 1 6 1070	 	
Yield: gal./min. with ft. drawdown after hrs.	00110 9/9		
" н	WATER RESOURCES DEPT		
" " "	SALEM, OREGON		
Bailer test 40 gal./min. with 15 ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 8/31 1979 Complete	ed 9/7	19 70
(9) CONSTRUCTION:	Date well drilling machine moved off of well	917	19 70
	Duilling Washing Orangian's Coulding the		
Well sealed from land surface toft_	Drilling Machine Operator's Certification: This well was constructed under my		vicion
Well sealed from land surface to	Materials used and information reported	above are true	to my
Diameter of well have below seed in	best knowledge and belief	$ \ln 4 $	79
Number of sacks of cement used in well sealsacks	[Signed] (Drilling Machine Operator)	Date 70/4	., 19
How was cement grout placed?	Drilling Machine Operator's License No.	329	
ORIGANAL SEAL NOT			··
DISTURBED	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi true to the best of my knowledge and beli	ction and this r	eport is
Was a drive shoe used? Yes No Piusi Size: location ft.	Name KELLER WELL DRILLING	5 G	
Did any strata contain unusable water? Yes Y No	(Person, firm or corporation)	(Type or prin	nt)
Type of water? depth of strata	Address 6350 SE BROWNIE	, IVIILWAU	KIE
Method of sealing strata off	[Signed]	_	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	actor)	
Gravel placed from ft. to ft.	Contractor's License No.462 Date	10/4	., 19
(USE ADDITIONAL SH	EETS IF NECESSARY)	87	*45858-119