WATER WELL REPORT

CLAC

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion. JUL 17 1964 STATE OF OREGON (Please type or print)

State Well No. ..... State Well No. ....

6-7-1 3-1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
(1) OWNER:	(11) WELL TESTS: Drawatown is amount water level is lowered below static level
Name John Mitsch	Was a pump test made? Yes \( \simega \) No If yes, by whom? driller
Address Rte 2 Box 34	Yield: 100 gal./min. with 45 ft. drawdown after 8 hrs.
Aurora, Oregon	<u>,,</u>
(2) LOCATION OF WELL:	n n n
County Clackamus Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.
1/4 1/4 Section 18 T. 4S R. 1E W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? ☐ Yes 🔀 No
	(12) WELL LOG: Diameter of well below casing
	Depth drilled 7 ft. Depth of completed well 109 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
TYPE OF WORK (check):	MATERIAL FROM TO
New Well □ Deepening ☑ Reconditioning □ Abandon □	Gravel and sand 102 103
If abandonment, describe material and procedure in Item 12.	Brown clay 103 109
(4) PROPOSED USE (check): (5) TYPE OF WELL:	
Domestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted	
Irrigation A Test Well Cother Dug Bored	
(6) CASING INSTALLED: Threaded □ Welded ☑	-
6" Diam. from	
"Diam. from	
"Diam. fromft. toft. Gage	
(7) PERFORATIONS: Perforated?  Yes  No	
Type of perforator used Millknife	
Size of perforations 3/8 in. by 1½ in.	
64 perforations from 98 ft. to 102 ft.	
perforations from ft. to ft.	
perforations fromft. toft.	
perforations fromft. toft.  perforations fromft. toft.	
perforations from	
(8) SCREENS: Well screen installed? ☐ Yes ₹ No	
anufacturer's Name	
Type Model No.	
Diam Slot size Set from ft. to ft.	Work started June 28 19 64 Completed July 1 1964
Diam, Slot size Set from ft. to ft.	0414
(9) CONSTRUCTION:	The second secon
· ·	(13) PUMP:
Well seal—Material used in seal	Manufacturer's Name Meyers
Diameter of well bore to bottom of sealin.	Type: Submersible H.P. 2
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ☐ Yes ☒ No	1
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Gravel placed fromft.	Tohn Maranan Maran
Did any strata contain unusable water? ☐ Yes ↓ No	NAME (Person, firm or corporation) (Type or print)
Type of water? Depth of strata	Address PO Box 42 Hubbard, Oregon
Method of sealing strata off	
	Drilling Machine Operator's License No. 277
(10) WATER LEVELS:	[Signed] Miller
Static level 43 ft. below land surface Date 7/1/64	(Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 26 Date July 15 , 1964
//ISE ADDITIONAL CON	THE PROPERTY OF THE PROPERTY O