CLAC 013338 - 18B(1)

File Original and First Copy with the STATE ENGINEER.

G1556

SALEM, OREGON ALEM. CORROLL	State Perint No.	<u> </u>	
(1) OWNER: Name John Mitsch	(11) WELL TESTS: Drawdown is amount lowered below static le Was a pump test made? A Yes	evel	
Name John Mitsch Address R 2 Box 34.	Yield: 40 gal./min. with 75 ft. drawdov	vn after 3 hrs.	
Aurora, Oregon.	220001 22 22 22 22 22	99	
	25 27 21		
(2) LOCATION OF WELL: County Clackamas Owner's number, if any—	Bailer test gal./min. with ft. drawdov	vn after hrs.	
NE% NE% Section 18 T. 4 S R. 1 E W.M.	Artesian flow g.p.m. Date	and a U Vog IV No	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis m	nade? 🗌 Yes 💹 No	
288 ft. 6 In. south and 21 ft. west	(12) WELL LOG: Diameter of well	6 inches.	
stone in the center line of county	Depth drilled 102 ft. Depth of completed v	well 102 ft.	
road set for the Northwest corner ##	Formation: Describe by color, character, size of mater	ial and structure, and	
of the Northeast Quarter of the North	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	change of formation.	
east Quarter os Sec. 18. T.4 S.R. I E	MATERIAL	FROM TO	
•	San d ;	0 65	
(3) TYPE OF WORK (check):	Coment grave	65 102	
New Well Ed Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 11.	Water	100 102	
If abandonment, describe material and procedure in Item 11.	-		
PROPOSED USE (check): (5) TYPE OF WELL:			
Domestic X Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐			
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐			
Inigation is rest well is even in page in pored in	_		
(6) CASING INSTALLED: Threaded ☐ Welded ☒			
6" Diam. from 0, ft. to 100 ft. Gage			
"Diam. fromft, toft. Gage			
" Diam. from ft. to ft. Gage			
		-	
(7) PERFORATIONS: Perforated? Yes No			
Type of perforator used			
SIZE of perforations in. by in.			
perforations fromft. tof	t.		
perforations fromft. tof			
perforations fromft. tof	t.		
perforations fromft. tof			
perforations fromft. tof			
(8) SCREENS: Well screen installed □ Yes ☒ No			
Manufacturer's Name			
Type Model No. Diam. Slot size Set from ft. to f	4		
h. Slot size Set from ft. to f		111 v 7 1959	
th, Slot size Set from It, w	work statted bully 1 13 14 completed to	<u>ury</u> /) 7	
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name E. E. Myers &	Bro. Co	
Gravel placed fromft. toft.	Type: Submersible		
Was a surface seal provided? 🗌 Yes 🔣 No To what depth? 1	t.		
Material used in seal—	Well Driller's Statement:		
Did any strata contain unusable water? Yes 5 No	This well was drilled under my jurisdiction	and this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.		
Method of sealing strata off	NAME John Truman Miller		
(10) WARRED I EXTER C.	(Person, firm, or corporation) (Type or print)		
(10) WATER LEVELS: Static level 48 ft. below land surface Date	Address P O Box 4 2 Hubbard	i, oregon	
Static level 40 ft. below land surrace Date Artesian pressure lbs. per square inch Date	_ Driller's well number	y Miller	
Log Accepted by:	[Signed]		
[Signed] John Mitschate July 28, 195	(Well Driller)	Ly 8 19 59	