NOTICE TO. WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CLAC

STATE OF OREGON

(Please type or print)

State Well No. 45/1E-21 bb

(Do not write above this line)

01344 (State Permit No. ...

(1) OWNER:	(10) LOCATION OF WELL:		
Vame John Vincent	County Clackamas Driller's well number 151		
Address 27094 S. Boland Rd.	NW 1/4 NW 1/4 Section 21 T. 4S R. 1E W.M.		
Canby, Or. 97013	Bearing and distance from section or subdivision	n corner	<u> </u>
(2) TYPE OF WORK (check):			
New Well 🛣 Deepening 🗌 Reconditioning 🗍 Abandon 🗌			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	112	ft.
Rotary X Driven Domestic Industrial Municipal	Static level 18 ft. below land st	urface. Date	4-12-8
Cable			
□ Bored □ Irrigation ★ Test Well □ Other □	Artesian pressure lbs. per square	e men. Bate	
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well b	elow casing	811
8 " Diam. from 0 ft. to 140 ft. Gage 1250	Depth drilled 155 ft. Depth of completed well 155 ft.		
7 OD " Diam. from 125 ft. to 155 ft. Gage 188	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratur	n and aquifer	penetrated,
(6) PERFORATIONS: Perforated? Types I No.	with at least one entry for each change of format position of Static Water Level and indicate prin	non, Keport eaci cipal water-bea	ring strata.
	MATERIAL	From To	SWL
Type of perforator used Torch	The state of the s		
Size of perforations 1/4 in. by 8 in.	Top soil	0 2 5	
48 perforations from 140 ft. to 150 ft.	Clay, brown Gravel, sand, black	5 18	
perforations fromft. toft.	Clay, brown	18 24	
perforations fromft. toft.	Gravel, clay, brown	24 33	
(7) SCREENS: Well screen installed? Yes No	Clay, sand, blue, black, fn.	33 39	
Manufacturer's Name	Gravel, cemented	39 53	
Type Model No.	Clay, sand, blue, black, fn.	53 112	
Diam Slot size Set from ft. to ft.	*Sandstone, black, fract.	112 119	
Diam Slot size Set from ft. to ft.	@lay,sand,blue,black,fn.	119 140	
(8) WELL TESTS: Drawdown is amount water level is	*Sandstone, black, fract.	140 155	
lowered below blatte tever			
Was a pump test made? XYes \(\subseteq \) No If yes, by whom? Driller	PROFILE		
1: 140 gal./min. with 37 ft. drawdown after 3 hrs.			1
n n n n	APR 2 3 1980		
" " " "			
Bailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DE	ੇ 1	
sian flow g.p.m.	SALEM, OREGON	<u> </u>	
Temperature of water Depth artesian flow encountered ft.	Work started 4-1 19 80 Complete	ed 4-12	19 8C
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-12	¹⁹ 80
Comont	Drilling Machine Operator's Certification:		
Well sealed from land surface to24ft.	This well was constructed under my	direct sup	ervision.
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above are tr	ue to my
Diameter of well bore below seal		Date4-2	1 ₁₉ 80
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		
How was cement grout placed? Pressure grouted from	Drilling Machine Operator's License No.	1030	
24 ft. to land surface.	Water Well Contractor's Certification:		
The state of the s	<u> </u>	iction and this	renort is
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? XYes \(\sum \) No_Plugs Size: location ft.	Name B & G Drilling (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)		
Type of water? depth of strata	Address 10030 S. Macksburg	na. Car	10y.,Q1 1
Method of sealing strata off	[Signed] Horge J Main	wright	~
Was well gravel packed? Yes Size of gravel:	(Water Well Contr		
Gravel placed fromft. toft.	Contractor's License No63.7 Date	<u> 4-21</u>	, 198.0