NOTICE TO WATER WELL CONTRACTED THE Original and first copy	T BEROPHIC 2 1972
A IT I WILL THE STATE OF THE ST	L REPORT 3 1973
AU filed with the STATE OF	OREGON TE ENGINESTATE, WELL NO 45/15-21
STATE ENCINEER, AADEM, OREGOSTAIDE ENGINEER (Please type within to days from the date	or print) ALLIV OR State Permit No.
of well completion. SALEM OREGORDO not write ab	ove this line)
	V.
(1) OWNER: 013445	(10) LOCATION OF WELL:
	County Clackarnas Driller's well number 7313
Name Sunk grais CAC	1/4 Section 2/ T. SHR. 1E W.M.
Address J. S. Dot 112/1	
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening 🗷 Reconditioning 🗓 Abandon 🗆	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Detine C Determ C	
Cable  Jetted  Domestic   Industrial   Municipal	Static level 27 6 ft. below land surface. Date 6-11-73
☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
(E) CACING INCHALLED.	
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below casing
F 12 "Diam. from + 1 6" ft. to 2586"ft. Gage : 250	Depth drilled 325 ft. Depth of completed well 258 6715
	Formation: Describe color, texture, grain size and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(a) DEDECT ACTONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? Yes \( \subseteq \) No.	
Type of perforator used torch	MATERIAL From To SWL
Size of perforations 36 in. by 6 in.	black sand clum chunes 216 220
480 perforations from 2186 ft. to 3586 ft.	black sand 220 232
perforations from ft. to ft.	dry sandy francley 232 240
perforations from ft. to ft.	gran Clar 240 325
(7) SCREENS: Well screen installed? ☐ Yes 🖫 No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	* perforated casing 338 wall
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	
gal./min. with ft. drawdown after hrs.	
" w/ an lift " "	
" "	4.
Bailer test 2/00 gal./min. with 146 ft. drawdown after & hrs.	
sian flow g.p.m.	
	Work started 4-25 1973 Completed 6-11 1973
Temperature of water Depth artesian flow encountered ft.	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-12 1973
· · · · · · · · · · · · · · · · · · ·	Drilling Machine Operator's Certification:
Well seal—Material used	This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my best knowledge and belief
Diameter of well bore to bottom of seal in.	73
Diameter of well bore below sealin.	Theillime Machine Operator)
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? 🗌 Yes 📆 No Plugs Size: location ft.	Name MID Schneider Equipment Co
Did any strata contain unusable water?   Yes  No	
Type of water? depth of strata	Address Star Kt, Doy 971, St. taul, Orc. 97137
Method of sealing strata off	Issued Mile & Knieler
Was well gravel packed? W Yes No Size of gravel: 34-3/4	[Signed] // (Water Well Contractor)
Gravel placed from	Contractor's License No. 387 Date 8-1 1973
GLUYOL PIGCOU LIVIII	, AU.V.