SINAL OF AREA WATER WILL BRILL	ERS REPORT   Do Not State Well No. 4/1F-21 M(1)
Original, and AUG I 7 1956 THE OF OPI	rant Fill In
STATE ENGINEER, STATE LINGINEER STATE OF OR	State Permit No.
SALEM OREGON 010 AM	(10) WELL TESTS:
(1) OWNER: Ivan Pulley	Was a pump test made? A Yes D No If yes, by whom? Driller
Dia On of Olive Chil	rield: 110 gal./min. with 68 ft. draw down after 3 hrs.
Address M. J. Carrier Con	" "
/2 × / 0 3	n n
(2) LOCATION OF WELL:	Artesian flowg.p.m.
County Clackenias Owner's number, if any—	Shut-in pressure lbs. per square inch.
R. F. D. or Street No. 13x 103	Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivision corner Part of the	Temperature of water 53 Was a chemical analysis made? ☐ Yes ☐ No
Andrew Gribble D.L.C. No. 11 in T. 1 S. R. 2 H7 FTE G 155 Ft S.	Was electric log made of well? ☐ Yes ☐No
OF The N.W. C. Drner.	(11) WELL LOG:
	Diameter of well, 611 inches.
(3) TYPE OF WORK (check):	Total depth 123 ft. Depth of completed well 123 ft.
New well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ Abandon ☐ Abandon ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:	O ft. to 3 ft. Top soil
Demostic & Industrial   Municipal   Rotary	3 " 9 " Grey silt
Cable	9 " 23 " Blue clay
Irrigation   Test Well   Other   Dug Well	23 " 38 " Cement gravel
CASING INSTALLED: If gravel packed	38 " 45 " Blue clay
Threaded □ Welded K Gage	45 " 63 " Green clay
FROM Oft. to 123 ft. 6 biam. 5/Wall Diameter of Bore ft. to ft.	63 " 71 " Dark green clay 71 " 86 " Light blue clay
FROM Off. to LED II. Oblam. Of Steam of Date	
11 11 11 11 11 11	86 " 91 " Dark brown clay 91 " 106 " Sand
n n n n n	106 " 110 " Pea gravel
11 11 11 11 11 11	110 " 122 " Silt gand & wood
11 11 11 11 11 11 11 11 11 11 11 11 11	122 " 123 " White clay
Type and size of shoe or well ring Standard Size of gravel:  Describe joint Butt Weld	1) 19
Describe joint Duot Wellu	n n
(7) PERFORATIONS:	11 11
Type of perforator used Ster	22 22
SIZE of perforations 1½ in., length, by 1/4 in.	19 19
FROM OAL to JL II. D Political L	n n
" 106 " 110 " <b>&amp;</b> " " 4 " " " " " " " " " " " " " " " "	1) ))
n n n n n n n n n n n n n n n n n n n	n n
n n n n n n n n n	11 11
SCREENS:	9. "
Give Manufacturer's Name, Model No. and Size	1) ))
	11 11
(8) CONSTRUCTION:	n 11
Was a surface sanitary seal provided?   Yes   No To what depth it.	n n
Were any strata sealed against pollution? Tes INo	Ground elevation at well sitefeet above mean sea level.
If yes, note depth of strata  FROM ft. to ft.	Work started July 23 1956, Completed July 31 19 56
n n	Well Driller's Statement:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
METHOD OF SEALING	
(9) WATER LEVELS:	NAME John W. Beck Well Drilling (Person, firm, or corporation) (Typed or printed)
Depth at which water was first found	Address Rt. 3, Box 45, Canby, Ore.
Standing level before perforating Bottom sealed it.	
Standing level after perforating	( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )
Log Accepted by:	(Well Driller)
[Signed] Svan Julley Dated aug ! , 1952	License No. 95 Dated July 31 , 1956
. Owner	