Duplicate with the	LL REPORT State Well No. 4/2-19 N (1)		
Duplicate with the STATE ENGINEER 013986 SALEM, OREGON 013986	OREGON GIJI 8 State Permit No	***************************************	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name / C/CP Wetten	Was a pump test made? ★ Yes ☐ No If yes, by whon		
Address	Yield: 120 gal./min. with 65 ft. drawdow		hrs.
Canby Orci	1) 2) 2)	<u> </u>	,,
(9) LOCATION OF WELL.	33 33		"
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown	n after	hrs.
County Clackamas Owner's number, if any—	Artesian flow g.p.m. Date		
½ ½ Section T. R. W.M. Bearing and distance from section or subdivision corner	Temperature of water 53.8 as a chemical analysis ma	ide? 🗌 Ye	s No
1598 14 & OF The S. W Corner		·	
Of Sec 19 THS RZE W.M.	100		inches.
- UT JEE IT TAS NEC W.III.	Depth drilled 180 ft. Depth of completed w		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ci	l and struc he materia hange of fo	ture, and I in each ormation.
Control of the Contro	MATERIAL	FROM	то
TYPE OF WORK (check):	Top soil	0	2
THE ST REP.	Brown clay & silt	2	21
New Well A Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 11.	Cement gravel, blue clay binder		
assument, describe indiction and procedure in their 11.	Cement gravel, brown clay binder	21 32	32 135
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue clay	135	145
Domestic 🔁 Industrial 🗌 Municipal 🔲 Rotary 🔲 Driven 🗆	Brown sand & gravel with brown	700	740
destion Communication Cable & Jetted C	clay binder	145	150
Igation Test went Other Dug Bored	Light blue clay		
(6) CASING INSTALLED: Threaded □ Welded X	Dark blue clay	150	165
6 "Diam. from ft. to 180 ft. Gage	Dark blue silt	165	170
"Diam. fromfttoft. Gage	Sand & fine gravel	170	179
	Denny & Time Stavel	179	180
(7) PERFORATIONS: Perforated? ♣ Yes □ No			
Type of perforator used Star			
SIZE of perforations $\frac{1}{4}$ in. by $\frac{1}{2}$ in.			
perforations from			
perforations fromft. toft.			
perforations from			
perforations from			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed ☐ Yes ☐ No			
ufacturer's Name			
Type Model No.	300		
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.	Work started Sept. 8 1957. Completed Se	ant 91	
200 000 000 000 000 000 000 000 000 000	Work Started 1700 1901. Completed De	SPO NT	19 57
CONSTRUCTION:	(13) PUMP:		
as well gravel packed? Yes No Size of gravel:	Manufacturer's Name Sumo	***************************************	
Gravel placed from ft. to ft.	Type: Submersible	H.P	3
Was a surface seal provided? Yes No To what depth? ft.			
Material used in seal—	Well Driller's Statement:		
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction a	and this re	eport is
Type of water? Depth of strata	true to the best of my knowledge and belief.		
Method of sealing strata off	NAME John W. Beck Well Drillin	g	
(10) WATER LEVELS:	(Person, firm, or corporation) (Ty	pe or print))
Static level 24 ft. below land surface Date 9/21/57	Address Rt. 3, Box 45, Canby, Ore	gon	*************
Artesian pressure lbs. per square inch Date	Driller's well number 395		
	Driller's well number	·····/	"
Log Accepted by:	[Signed] TOMM (N)	2K.	
[Signed] Date Wes 6, 1957	(Well Driller)		
(Owner)	License Nb 95 Date Sep	t. 21	, 1957
(USE ADDITIONAL SE	EETS IF NECESSARY)		