DECEIVE Dwell#2

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WATER WELL REPORT A OREGON 4

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print) 6-4228

State Permit No. ....

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Dick Moorehouse	Was a pump test made? K Yes □ No If yes, by whom		
Address Molalla, Oregon	Yield: 500 gal./min. with 57 ft. drawdow	n after	4 hrs.
(2) LOCATION OF WELL:	" " "		"
County Clackamus Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.		
77	Artesian flow g.p.m. Date		
31 T. 4S R. 2E W.M.	Temperature of water Was a chemical analysis made?   Yes X No		
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below case	sing	
	700	70	Λ.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.		
(a) MADE OF MODE ( )	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Soil	0	3
New Well  ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Brown: clayel	3	8
andonment, describe material and procedure in Item 12.	Cement gravel	8	134
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown sticky clay	134	146
Domestic   Industrial   Municipal   Rotary   Driven	Blue sandy clay	146	161
Irrigation  Test Well  Other	Gravel	161	163
Dug 🔲 Bored 🖂	Blue sandy clay	163	181
(6) CASING INSTALLED: Threaded □ Welded □	Coarse red sand	181	186
12 Diam from 0 ft to 168 ft Gage 1/4"	Shale rock (blue)	186	228
8 " Diam. from 165 ft. to 320 ft. Gage 14"	Sticky shale	228	247
ft. Gage	Grey sandy clay	247	255
(7) DEPENDRATIONS		255	260
1	Brown sandy shale	260	282
Type of perforator used Millknife	Sand	282	290
Size of perforations 3/8 in. by 4 in.	Blue shale	290	300
50 perforations from 65 ft. to 69 ft. 81 perforations from 82 ft. to 89 ft.	Grey shale	300	315_
64 120 126	Blue shale	_315	320
70 129 127	Additional perforations		
9		(¼" x	12")
	15 perforations from 179' to 18		
(8) SCREENS: Well screen installed? ☐ Yes 💆 No	20 perforations from 255' to 26		
Manufacturer's Name	10 perforations from 280' to 28		
Tee Model No.	10 perforations from 299' to 30		/\
h Slot size Set from ft. to ft.	Work started January 1019 67 Completed Apr	il 20	67
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well Apr		
(9) CONSTRUCTION:	(13) PUMP:	11 20	19 67
Well seal—Material used in seal Puddled Mud	Manufacturer's Name		
Depth of seal 20 ft. Was a packer used? no	Туре:		
Diameter of well bore to bottom of seal in.	л	.F	***************************************
Were any loose strata cemented off? Twes I No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ₩ Yes □ No =	This well was drilled under my jurisdiction as	nd this	renort is
Was well gravel packed? Tyes K No Size of gravel:	true to the best of my knowledge and belief.	TO VALLE .	report 13
Gravel placed from ft. to ft.	NAME John Truman Miller		
Did any strata contain unusable water? 🛛 Yes 😿 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P O Box 42 Hubbard, Oregon		
Method of sealing strata off	D. 1111 16 26		
(10) WATER LEVELS:	Drilling Machine Operator's License No. 26		
Static level 21 ft. below land surface Date 4/20/67	[Signed] (Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 277 Date April 2	21	<sub>19</sub> 67
USE ADDITIONAL SH			., 10