CLAC well #1

014258

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED MAY 11 1966 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

G-4228
G-3622

State Well No. 4/2-31Q

State Permit No.

(1) OWNER:
Name Dick Moorehouse
Address Rte 1
Hubbard, Oregon

(2) LOCATION OF WELL:
County Clackamus Driller's well number
¼ ¼ Section 31 T. 4S R. 2E W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☐ Welded ☒
16" Diam. from 0 ft. to 160 ft. Gage ¼"
12" Diam. from 0 ft. to 212 ft. Gage ¼"
8 5/8" Diam. from 205 ft. to 325 ft. Gage ¼"

(7) PERFORATIONS:
Perforated? ☒ Yes ☐ No
Type of perforator used Millknife and torch
Size of perforations 3/8 in. by 4 in.
40 / 56 perforations from 44 / 60 ft. to 46 / 64 ft.
104 / 144 perforations from 82 / 95 ft. to 89 / 105 ft.
144 / 64 perforations from 119 / 142 ft. to 129 / 146 ft.
48 / 56 perforations from 135 / 139 ft. to 138 / 139 ft.
(¼ x8") 40 / 200 perforations from 147 / 252 ft. to 150 / 282 ft.
106 / 64 — 135 / 130 — 135 / 135

(8) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Puddled Mud
Depth of seal 20 ft. Was a packer used? no
Diameter of well bore to bottom of seal 24 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 32 ft. below land surface Date 4/30/66
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? driller
Yield: 500 gal./min. with 88 ft. drawdown after 8 hrs.
" 900 " 118 " 8 "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG:
Diameter of well below casing
Depth drilled 325 ft. Depth of completed well 325 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Surface	0	2
Brown clay	2	12
Cement gravel & boulders	12	109
Clay	109	117
Cement gravel & boulders	117	129
Sand	129	138
Clay	138	139
Sand	139	141
Sticky clay	141	141'6"
Gravel	141'6"	147
Sand	147	155
Gravel	155	160
Brown clay	160	168
Cement gravel	168	178
Blue shale rock	178	255
Black coarse sand	255	270
Shale with sand streaks	270	325

Work started Feb 1966 Completed April 30 1966
Date well drilling machine moved off of well 19

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller (Person, firm or corporation) (Type or print)
Address P O Box 42 Hubbard, Oregon
Drilling Machine Operator's License No. 26
[Signed] John Truman Miller (Water Well Contractor)
Contractor's License No. 277 Date May 4, 1966

(USE ADDITIONAL SHEETS IF NECESSARY)