The original and first copy of this report AC are to be filed with the	LL REPORT RECEIVE DI No.	1/2/20 27 h
WATER RESOURCES DEPAREMENT AS SALEM, OREGON 97310 within 30 days from the date	OREGON LUC State ven No.	
of well completion.	bove this line)	io
THATER RESOURCES DEPT	WATER RESOURCES DEPT	
(1) OWNER: SALEM, OREGON	(10) LOCATION MODIFIED H	
Name Shady Dane Farm	County Clackamas Driller's well number	
Address Rt. 3, Box 144 Molalla, Oregon 97038	NW 14 14 Section 32 T. 4S R. 2E W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well Deepening Reconditioning Abandon II If abandonment, describe material and procedure in Item 12.	(11) WAMED LEVEL Comments	- 91
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w	7 e11. 86
Rotary Driven Domestic Industrial Municipal D	Depth at which water was first found	8/27/7
	Static level ft. below land s	surface. Date
	Artesian pressure lbs. per squar	re inch. Date
(5) CASING INSTALLED: Threaded Welded 12 Welded 250 ft. to 342 ft. Gage 250	(12) WELL LOG: Diameter of well below casing	
Diam. from ft. to ft. Gage ft. Gage ft. Gage	Depth drilled 382 ft. Depth of compl	eted well 353 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size	and structure of materials;
	and show thickness and nature of each stratu with at least one entry for each change of forma	tion. Report each change in
(6) PERFORATIONS: Perforated? Yes I No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used Mills knife	MATERIAL	From To SWL
Size of perforations 3/8 in. by 21/2 in. 550 86 174	Top soil	0 2
perforations from 201 ft. to 210 ft. perforations from 201 ft. to 210 ft.	Clay, tan	2 12
perforations from ft. to ft.	Gravel Clay brown	12 28
130 perforations from 6t to 174 ft. 130 perforations from 22 ft to 210 ft. 200 perforations from 248 ft to 261 ft.	Gravel med. cemented	28 50 50 75
(7) SCREENS: Well screen installed? Yes No	Clay, brown	75 82
Manufacturer's Name	Clay, blue	82 86
TypeModel No.	Gravel, med. some clay	86 102 WB
Diam. Slot size Set from ft. to ft.	Gravel med. sand	102 140 WB
Diam. Slot size Set from ft. to ft.	Gravel, med.	140 170 WB
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay, grey, small gravel Sand, black, med.	170 203 203 207 WB
a pump test made? [Yes No If yes, by whom?	Clay, brown	207 236
Yre d: gal./min. with tt. drawdown after hrs.	SAnd, black	236 238 WB
и. и и	Clay, grey	238 250
**************************************	Sand, black, med.	250 258 WB
A1r 350 320 ft. drawdown after hrs.	Clay, blue, gravel Claystone, blue	258 316
stan flow g.p.m.	Claystone, blue Claystone, black to blue	316 347 382 WB
Temperature of water Depth artesian flow encounteredft.	7/3 79	8/27/70
	Work started 19 Complete	d 8/27 19 19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	
Well seal—Material used Coment	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	direct supervision.
Diameter of well bore to bottom of seal a	best knowledge and belief	- ·
Diameter of well bore below seal in. 40 Number of sacks of cement used in well seal sacks	[Signed] Dynn D. Malla I	Date 8/28, 1979
How was cement grout placed?	Drilling Machine Operator's License No.	1371
Pressure grout		· · · · · · · · · · · · · · · · · · ·
The second secon	Water Well Contractor's Certification:	+ + • = = 2
	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and this report is
Was a drive shoe used? Yes No Plug. Size: location ft.	Name C. G. Westerberg	
Did any strata contain unusable water T Ves No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address Rt. 1, Box 151, Mulino, Oregon	
Method of sealing strata off	[Signed] Color State Stay	
Was well gravel packed? Yes No. Size of gravel:	(Water Well Contrac	
Gravel placed from ft. to ft.	The state of the s	8/28 , 1879
(USE ADDITIONAL SHI	EETS IF NEGEGGARY	