

NOTICE TO WATER WELL CONTRACTOR

The original and file copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED MAR 3 11 1969 STATE ENGINEER

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

CLAG 014296

State Well No. 4/2-32 dd

State Permit No.

G5268

(1) OWNER:

Name Wesley Hamilton Address Route 2, Box 495, Molalla, Ore. 97038

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 107 ft. Gage 0.250 5.9/160 Diam. Laser 104 ft. to 116 ft. Gage .10

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used Torch Size of perforations 1/8 in. by 12 in. 18 perforations from 105 ft. to 115 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 18 ft. below land surface Date 3-15-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 35 gal./min. with 64 ft. drawdown after 1 hrs. Artesian flow g.p.m. Date Temperature of water 53° Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal-Material used Bentonite Depth of seal 34 ft. Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Clackamas Driller's well number 14-69 NE 1/4 SE 1/4 Section 32 T. 4S R. 2E W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing Depth drilled 116 ft. Depth of completed well 116 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Clay, tan; Clay and gravel, tan; Gravel and boulders, cemented; Clay, tan; Gravel, cemented; Clay, sandy, grey.

Work started Mar. 4 19 69 Completed Mar. 15 1969 Date well drilling machine moved off of well Mar 17 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Robert E. McConnell Date Mar. 21, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 398

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Steinman Bros. (Person, firm or corporation) (Type or print)

Address 15112 S.E. McLoughlin, Milwaukie, Ore. 97222

[Signed] Robert E. McConnell (Water Well Contractor)

Contractor's License No. I Date March 21, 1969