NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

CLAC 014548

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED OCT 27 1972 STATE ENGINEER SALEM, OREGON

State Well No. 3S/4E-22 C
State Permit No.

(1) OWNER:
Name A. J. HANSON
Address 5335 S.E. Brookside Dr. Portland Oregon

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:
Threaded [ ] Welded [X]
6" Diam. from 0 ft. to 102 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? [ ] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [ ] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
Bailer test 7 1/2 gal./min. with 20 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 51° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout 5% Bent.
Well sealed from land surface to 32 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [ ] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number
NW SW Section 22 T. 3S R. 4E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 98 ft.
Static level 62 ft. below land surface. Date 9/30/72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 106 ft. Depth of completed well 106 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Overburden	0	3	
Clay Brown	3	50	
Clay Purple	50	65	
Clay Blue	65	95	
Sand Coarse	95	106	

Work started 9/28 1972 Completed 9/30 1972
Date well drilling machine moved off of well 10/1 1972

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Donald C. Fouman (Drilling Machine Operator) Date 10/1, 1972
Drilling Machine Operator's License No. 231

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name F & S Well Drilling (Person, firm or corporation) (Type or print)
Address Rt. 3 Box 488 Estacada
[Signed] Donald Fouman (Water Well Contractor)
Contractor's License No. 477 Date 10/1, 1972

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119