NOTICE TO WATER WELL CONTRACT NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97810.

STATE OF OREGON within 30 days from the date of well completion.

APR-23 19 WATER WELL REPORT

State Permit No. ..

	•		and the second s	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Barney Lucas	Was a pump test made? Yes ☐ No If yes, by whom		nan Bros	
Address RT2 Box 600	Yield: //5 gal./min. with 72 ft. drawdov		hrs.	
Estacada Ore	2) 3)		* 11	
(2) LOCATION OF WELL:	23	<u> </u>	97 The state of the Sales	
County Chacka Mass Driller's well number 1/65	Bailer test gal./min. with ft. drawdo	wn after	hrs.	
56% N % Section 24 T. 35 R. 46	Artesian now g.p.m. Date			
Bearing and distance from section or subdivision corner	Temperature of water 3 Was a chemical analysis i	nade? 🔲 🦠	Yes No	
	(12) WELL LOG: Diameter of well below c	asing		
	Depth drilled /30 ft. Depth of completed w	ell / E	3 D ft.	
	Formation: Describe by color, character, size of materic show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru the mater	cture, and lal in each	
	MATERIAL			
(3) TYPE OF WORK (check):	Chay Brown	FROM	TO	
New Well Deepening 🗌 Reconditioning 📙 Aba	ndon []		4	
andonment, describe material and procedure in Item 12.	cement grove / Brown	41	16	
(4) PROPOSED USE (check): (5) TYPE OF W		7	19	
Potenty II Dutyo	Piltota D	110	25	
Cable A Jetted		740		
Irrigation Test Well Other Dug Bored	Cement grave 1 & Boulders	25	38	
(6) CASING INSTALLED: Threaded Welded	21 -			
6 " Diam. from 0 ft. to 130 ft. Gage 1 6	250 Sandy Chay Brown	38	61	
" Diam. fromft. toft. Gage	0			
"Diam, fromft. toft. Gage	Brown Sandy chay	61	70	
(7) PERFORATIONS: Perforated? Yes No	V. State of the st			
Type of perforator used Mills Khife	Sandagrove/ Fine	70	77	
Size of perforations /// in. by 2 in.	Mellows & Down Com	17 /7	O e me	
7~ 7 75 77	yellowand Brown Sond	7/	<u>-85</u>	
15 perforations from 35 ft. to 88	sanda grave Brown	85	رای هست	
60 perforations from //2 ft. to /20	6 ft.	_ 00		
perforations from ft. to	ecment sanda grove)	88	112	
perforations from ft. to	entraceft.			
(8) SCREENS: Well screen installed? ☐ Yes Y No	grey SANdsTone	1/2	13/3	
Manufacturer's Name			· · · · · · · · · · · · · · · · · · ·	
Type Model No.	grey chay	126	130	
Slot size Set from ft. to	ft.			
Diam. Slot size Set from ft. to	Work started 3/6/2519 . Completed 5	120	1805	
(9) CONSTRUCTION:	(13) PUMP:	13/6	5 19	
Queto ita	(10) 1 01111.			
	Manufacturer's Name	······	P. A. Charles Tax and T. FE	
Depth of sealft. Was a packer used?ft. Diameter of well bore to bottom of sealin.	Type:	Type: H.P.		
Were any loose strata cemented off? ☐ Yes No Depth	Water Well Contractor's Certification:			
Was a drive shoe used? Yes ☐ No	Order and Control of the Control of			
Was well gravel packed? ☐ Yes X No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	nd this r	eport is	
Gravel placed fromftft.		_ "		
Gravel placed from ft. 6 ft. NAME Stein Mo (Person, firm or corporation) (Type or print)				
Type of water? denth of strata	Address Milwoupie 12 Dre			
Method of sealing strata off		/		
(10) WATER LEVELS:	Drilling Machine Operator's License No	7		
ED	11 - [Signed] Sleinman Bro.	1		
Static level 6 of ft. below land surface Date 3/18. Artesian pressure lbs, per square inch Date	(Water Well Contractor)			
	Contractor's License No. Date	2/6	5 19	
COSE ADDITIO	INAL SHEEP'S IT MECECOADM	_		

(USE ADDITIONAL SHEETS IF NECESSARY)