NOTICE TO WATER WELL CONTINCE E WATER WEI are to be filed with the	- fex W/M# 16	1817		\$8
water resources department, APR 8 1980 STATE OF	OREGON N L V L State Well No.	3\$/4	E-0	Lede
SALEM, OREGON 97310 within 30 days from the WATER RESOURCES DEPT AUG 20 1980 of well completion. SALEM, OREGON WATER RESOURCES DEPT WATER RESOURCES DEPT WATER RESOURCES DEPT				
(1) OWNER:	(10) LOCASION OF WELL:	$-\epsilon$		
· ·	County Clackamas Driller's well number			
— With I Little III . Dietally CI		number R. 4E		
Address 3203 S.E. Vineyard Rd. Milwaukie OR 97222				<u> W.M.</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well	Lakehead Trailer Court			
If abandonment, describe material and procedure in Item 12.	Rt 3 Box 344 Estacada OR 97023			
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 Static level 30 ft. below land surface. Date 3/24			
Domestic Industrial Municipal				24
Dug	Artesian pressure lbs. per square inch. Date			
(E) CACING INSMALL ND.	- Political Control of the Control o			······································
(5) CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well below casing 6			
6" Diam. from	Depth drilled 80 ft. Depth of completed well 80 ft.			
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;			
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
(6) PERFORATIONS: Perforated? (X Yes ☐ No.	position of Static Water Level and indicate pri	ition. Kep ncipal wa	ort each (ter-bearir	change in 1g strata.
Type of perforator used Cutting Torch	MATERIAL	From	То	
Size of perforations ½ in. by 10 in.		From		SWL
24 perforations from 53 ft. to 59 ft.	Overburden	 U	4	
perforations fromft. toft.	Clay Brown	4	12	
perforations fromft. toft.	Clay Diown	 '- -	12	
	Clay Brown w/boulders	12	26	
(7) SCREENS: Well screen installed? Yes X No	- July Divil W/ Dourders	1-1-	20	
Manufacturer's Name	Clay light gray	26	35	
Type Model No.				- 7500
Diam. Slot size Set from ft. to ft.	Rock gray fractured	35	53	
Diam, Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Rock gray	5.3	60	
a pump test made? Yes No If yes, by whom?	Rock gray w/seams	60	80	
Yield: \$40 gal./min. with ft. drawdown after hrs.				
" Air Test " " "	<u> </u>			
" " " "				
ler test gal./min. with ft. drawdown after hrs.		ļ		
Artesian flow g.p.m.		<u> </u>		
Temperature of water 53 Depth artesian flow encountered	1 00	<u> </u>		
1. T.	Work started March 22 1980 Complete		ch 26	<u> 19 8 ()</u>
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3	/26		¹ 80
Well seal—Material usedCement Grout	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal 12 in.	Materials used and information reported best knowledge and belief.	above a	are true	to my
Diameter of well bore below seal	[Signed] Date 3/26, 1980.			
Number of sacks of cement used in well seal sacks				
How was cement grout placed?Air Pump	Drilling Machine Operator's License No.		23.L	*********
The Control of the Co	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? XYes No Plugs Size: location ft.				
Did any strata contain unusable water? X Yes \(\square\) No	Name Don Foreman Drilling (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P 0 Box 296			
Method of sealing strata off		************		,
Was well gravel packed? ☐ Yes ♥ No Size of gravel:	[Signed] (Water Well Contractor)			
Gravel placed fromfttoft	· · •	-		۸۵.
Gravel placed from ft. to Contractor's License No. 477 Date 3/26 , 180				