WATER WELL REPORT
STATE OF OREGON

RECEIVED
NOV 5 1980
WATER RESOURCES DEPT
SALEM, OREGON

CLAC 014728

State Well No. 3s/4e-28

State Permit No. .....

(1) OWNER:

Name Bill Stanyer
Address 3405 S.E. Vineyard Rd.
City Milwaukie, State OR

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Air ☒ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:

Steel ☒ Plastic ☐
Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 43 ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

4" Diam. from 40 ft. to 105 ft. Gauge 160 PVC

(6) PERFORATIONS:

Perforated? ☒ Yes ☐ No
Type of perforator used Saw
Size of perforations 1/8 in. by 5 in.
80 perforations from 60 ft. to 80 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
Air test 27 gal./min. with drill stem at 100 ft. 2 hrs.
Bailer test " gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒
Well seal—Material used Cement
Well sealed from land surface to 22 ft.
Diameter of well bore to bottom of seal 10+ in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 17 sacks
How was cement grout placed? Pumped

Was pump installed? No Type HP Depth ft.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number
¼ ¼ Section 28 T. 3s R. 4e W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: RT.3 ESTACADA, OREGON

(11) WATER LEVEL: Completed well.

Depth at which water was first found 75 ft.
Static level 42 ft. below land surface. Date 10/17/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 105 ft. Depth of completed well 105 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown soil	0	7	
Brown clay	7	21	
Gravel	21	32	
Rock soft gray-green	32	46	
Cemented gravel -water-	46	105	42

Work started 10/15 1980 Completed 10/17 1980
Date well drilling machine moved off of well 10/17 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] David Wyland (Drilling Machine Operator) Date 10/24 1980

Drilling Machine Operator's License No. 1396

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name D.V.Wyland & Co. Inc. (Person, firm or corporation) (Type or print)
Address 16150 S.E. Norma Rd. Milwaukie, OR
[Signed] Daniel Wyland (Water Well Contractor)
Contractor's License No. 554 Date 10/24, 1980

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690